



# MORBARK®



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

# C-SERIES LOG DEBARKER

The **Morbark C Series Debarkers** will debark logs from 4" to 24" (10.2 cm – 61 cm) in diameter and up to 70' (21.3 m) in length. Using the Morbark Debarking Principle, the C series is effective in debarking hardwood and softwood, including stringy species, making it popular in cedar mills. To process logs end to end, a unique infeed rollcase allows the operator to load a log onto the infeed table while another is being debarked. This Debarker is built with hourglass rollcase-type infeed and outfeed conveyors. All functions are controlled from the operator's cab. The machine's hydraulic system is sufficient to power most infeed decks and debarker waste conveyors. This unit is generally used in barn pole, fence post and log home industries.

## FEATURES AND BENEFITS

- Hourglass rollcase type infeed and outfeed conveyors
- 8' to 20' (2.4 m – 6.1 m) infeed and outfeed sections complete with steel support legs and kicker assemblies
- Outfeed conveyor has (1) set of hydraulic two-way kickers
- Self-contained hydraulic system complete with operator's controls
- Hydraulic table lock assembly, variable speed drive and infeed shoe
- Adjustable infeed post
- Legs are 34" (86.4 cm) to the top of infeed rolls
- Motor base (frame size must be a minimum of 75 hp/55.9 kW) and V-belt drive
- 3-pump hydraulic system. All machine functions are completely hydraulically controlled with a variable speed on the feed wheels

[MORBARKDEALERS.COM](http://MORBARKDEALERS.COM)



# MORBARK®



# MORBARK® C-SERIES DEBARKER SPECIFICATIONS

GENERAL	US	METRIC
Capacity (diameter range)	4" – 24"	10.2 cm – 61 cm
Capacity (length)	8' – 70'	2.4 m – 21.3 m
Power	75 hp or 100 hp electric (diesel available)	55.9 kW or 74.6 kW
Production rate	40 FPM (peeling)	12.2 m/min
Infeed/Outfeed	8' – 70' lengths	2.4 m – 21.3 m
Debarker	Patented Morbark system floating cutterhead	

## OPTIONS INCLUDE

- Available Models: C-8, C-12, C-16, C-24, C-40, C-50, C-60, and C-70
- Peeler package including hard rubber tire on the outer drive wheel and split peeler type cutterhead
- Hydraulic adjustable infeed post to accommodate crooked material
- Heavy-duty debarker drive with 10,000 Series Char-Lynn Motor (heavy duty drive increases log turning power and is recommended for the Model C-24 and C-70 Debarkers)
- Elevated operator's console, complete with access ladder, seat, valve bank and hose hook-up
- All-weather operator's cab. Cab is 54" wide x 58" x long x 6'8" tall (137.2 cm x 147.3 cm x 2 m) and includes two side sliding windows for cross ventilation
- Side-mounted combination air conditioner/ heater unit for cab enclosure
- Blower and auger for bark removal

Specifications may vary with equipment options

Updated 2/26/2020

