



MORBARK®



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

CHIP-PACS

The **Morbark Chip-Pac** combines chipping, screening and chip loading into one self-contained package. Morbark chip screens are proven high-capacity machines that separate overs and fines from acceptable chips. With a rugged Morbark chipper at its heart, the Chip-Pac, available in 48" and 58" (121.9 cm and 147.3 cm) sizes, is extensively used to sawmill waste. Chip-Pacs are available with a 10-hp (7.5 kW), 30-hp (22.4 kW) or 40-hp (29.8 kW) chip blower, plus an optional 3-hp (2.2 kW) fines blower.

FEATURES AND BENEFITS

- Blowpipe and Cyclone
- Overs return to chipper spout
- Double pump hydraulic system includes oil tank, valve bank, chipper sheave, and bushing, less base (D Model)
- Motor base including belt shield and take-up rails (E Model)
- Screen mounts above chipper for no wasted space
- Acceptable chips are able to be discharged on either side of the Chip-Pac
- Flexible rods support the screen; no knuckle joints are used





SPECIFICATIONS	US	METRIC
48" (121.9 CM) CHIP-PAC SPECIFICATIONS		
Power	75-hp to 150-hp electric or diesel	55-9 kW – 111.8 kW
Capacity	11" Diameter	27.9 cm Diameter
Weight	11,200 lb	5080 kg
Width	76"	193 cm
Depth	70"	177.8 cm
Height	92"	233.7 cm
Space Required	23" – 110"	58.4 cm – 279.4 cm
Screen	5' x 5' (1.5 m x 1.5 m) with 2-hp (1.5 kW) hydraulic or electric drive	
Foundation	Cement slab	
58" (147.3 CM) CHIP-PAC SPECIFICATIONS		
Power	75-hp to 250-hp electric or diesel	55-9 kW – 186.4 kW
Capacity	15" Diameter	38.1 cm Diameter
Weight	15,640 lb	7094 kg
Width	88"	223.5 cm
Depth	87"	221 cm
Height	146"	380.4 cm
Space Required	155" – 110"	393.7 cm – 279.4 cm
Screen	6' x 6' (1.8 m x 1.8 m) with 2-hp (1.5 kW) hydraulic or electric drive	
Foundation	Cement slab	

OPTIONS INCLUDE

- 3-hp fines blower with 3-hp (2.2 kW) electric motor mounted on swivel base
- Hydraulic or electric 10-hp (7.4 kW) chip blower mounted on swivel base with single "S" pipe
- Hydraulic or electric 30-hp (22.4 kW) super blower mounted on swivel base with single "S" pipe
- Hydraulic 40-hp (29.8 kW) chip blower mounted on a fixed base with dual "S" pipes and "Y" valve for dual loading (58"/147.3 cm model only)
- Convert horizontal feed to drop feed chipper
- Convert 3-knife to 4-knife or 6-knife chipper

Specifications may vary with equipment options

Updated 2/26/2020