



Lubie® 200 Bed Lube

A blended formulation of synthetic lubricants in a fast evaporating solvent carrier. #200 is formulated to reduce friction, decrease heat and prevent wood resin build up on moulder beds, planer beds and other wood transfer equipment.

Lubie® 200 dries very quickly, leaving a durable lubricating film on the bed. Wood staining, painting, laminating and other finishing operations generally are not affected because there is no silicone, grease or wax used in the formulation.

Lubie® 200 is designed for use in automatic, semi-automatic and manual bed injector systems. The very low viscosity allows it to also be used in spray bottles.

PHYSICAL DATA

Raw Material Base	Petroleum Hydrocarbon	Color	Light Yellow
Boiling Point	300°F	Specific Gravity	0.813
Flash Point	135°F (COC)	Freeze Point	N/A
Percent Volatiles by Weight	90%	Lubricity Rating	0.035 (diesel fuel=0.074)
Solubility	None	Odor	Light Petroleum

USED ON:

Moulders by: Weinig, Wadkins, Yates, Madison, Tri State and Diehl.

Package Saws: Holtec, L&M.

UNIT (Gallons)	CATALOG #
CASE (4 Gallons)	BL 200-1
PAIL (5 Gallons)	BL 200-5
DRUM (55 Gallons)	BL 200-55



Smith Sawmill Service
181 County Road 4763
Timpson, TX 75975 USA
Phone: 1-800-598-6344
Fax: 936-354-3975
sawmill.shop
info@smithsawmillservice.com

