



## Biolube 2

A synthetic oil blend that will not get gummy or burn on the blade. Biolube 2 is designed to lubricate, cool, and retard resin and pitch build-up on band saw blades, circular saw blades, and other wood tooling. Biolube 2 provides over twice the lubricating strength of diesel fuel. Many mills use #2 to lubricate the headrig ways and carriage wheels and rails. Biolube 2 is low cost, odorless, non-irritating to skin, nontoxic and environmentally friendly. #2 does not contain silicones and will not stain or discolor wood.

Biolube 2 replaces diesel fuel in spray, drip, and wick systems. Mills using about 2 quarts per shift of #2 find the cost lower than diesel fuel while eliminating the fire hazard, personal safety, and odor problems of diesel.

Biolube 2 is most effectively applied through Biolube spray systems which give the ultimate in application and volume adjustment. Wick, drip, and other spray systems run #2 effectively.

Biolube #2 is nontoxic, biodegradable, non-irritating, and has FDA approval. It does not contain any chemicals listed in SARA Title III, Section 313, or in OSHA 29 CFR 1910.

### PHYSICAL DATA

Raw Material Base	Ester Oil	Color	Clear / Light
Boiling Point	N/A	Specific Gravity	0.837
Flash Point	>143°C, >290°F	Freeze Point	N/A
Percent Volatiles by Weight	N/A	Lubricity Rating	0.039 (diesel fuel=0.074)
Solubility	100%	Odor	None
<b>USED ON:</b>		Pour Point	-46°C, -50°F

Gang Rip Saws by: Mereen-Johnson, SCMI, Cornell, Diehl, Brewer and Yates.

Band Saws by: McDonough, Salem, Filer & Stowell, Wheiland, Brewer, Kimwood, Ferrari, Forestor.

UNIT (Gallons)      CATALOG #

DRUM (55 Gallons) BL 2-55



**Smith Sawmill Service**  
181 County Road 4763  
Timpson, TX 75975 USA  
Phone: 1-800-598-6344  
Fax: 936-354-3975  
sawmill.shop  
info@smithsawmillservice.com

