



Lubie[®] 43 Concentrate

Lubie[®] 43 is a concentrated water based floropolymer lubricant/coolant/cleaner generally diluted to a 10% solution with water that is very effective on all thin kerf circular saws, finger joint knives and moulders knives. Lubie^{®4} 3 is formulated to prevent heat and pitch build-up on thin kerf tooling. Customers report thin kerf saws do not over heat and distort and that finger joint knives and molder tooling runs longer with less tear-out.

- Lubie 43 is non flammable, non toxic and biodegradable.
- It does not contain any chemicals listed in SARA Title III, Section 313 or in OSHA 29 CFR 1910.
- #3 does not contain silicones and will not stain or discolor wood.

Lubie[®] 43 is most effectively applied diluted at 10:1 with water through Biolube's Lubie[®] spray systems, which give the ultimate in application and volume adjustment. Other spray systems have also run #43 effectively.

PHYSICAL DATA

Raw Material Base Waterbased Emulsion Color Milky White

Boiling Point >100C, 212°F Specific Gravity 1.0

Flash Point None Freeze Point 0°C, 32°F

Percent Volatiles by Weight N/A Lubricity Rating 0.032 (diesel fuel=0.074)

Solubility 100% Odor None

USED ON:

Finger Jointers by: Western Pneumatics (Aceco and Wisconsin Tooling).

Gang Rip Saws by: Mereen-Johnson, SCMI, Cornell, Diehl, Brewer and Yates.


Band Saws by: McDonough, Salem, Filer & Stowell, Wheiland, Brewer, Kimwood, Ferrari,

Forester.

Moulders by: Weinig, Wadkins, Madison, Tri State and Diehl.

UNIT (Gallons) CATALOG #

CASE (4 Gallons) BL 43-1 PAIL (5 Gallons) BL 43-5 DRUM (55 Gallons) BL 43-55



Smith Sawmill Service

181 County Road 4763 Timpson, TX 75975 USA

Phone: 1-800-598-6344

Fax: 936-354-3975 sawmill.shop

info@smithsawmillservice.com

