



The home of Lubie® saw lubricating systems and Lubie lubricants.

Lubie® 9

A concentrated waterbased high-grade synthetic lubricant designed to be diluted with water. Lubie® 9 is formulated to provide maximum lubrication on band and circular saws. Additionally, #9 cools and retards resin build-up along with providing outstanding rust and corrosion protection.

Lubie® 9 is commonly used as a high performance lubricant, coolant and cleaner on band saws and edgers. When diluted 5:1 to 10:1 with water it provides better cleaning and lubrication than diesel fuel at the same cost per shift and eliminates the fire hazard, odor, personal safety and environmental problems of diesel fuel. #9 does not contain silicones and will not stain or discolor wood.

Band saws find Lubie® 9 is most effectively applied through Biolube spray systems. #9 can also be used in wick or drip lubrication systems.

Lubie® 9 is non-flammable, non-toxic and biodegradable. It does not contain any chemicals listed in SARA Title III, Section 313 or in OSHA 29 CFR 1910.

IMPORTANT NOTE; Always add #9 to water.

PHYSICAL DATA

Raw Material Base	Synthetic Emulsion	Color	Light Yellow
Boiling Point	100°C, 212°F	Specific Gravity	0.982
Flash Point	None	Freeze Point	0°C, 32°F
Percent Volatiles by Weight	<3%	Lubricity Rating	0.035 (diesel fuel=0.074)
Solubility	100%	Odor	Light Pine
USED ON:		Pour Point	-81°C, -90°F

Gang Rip Saws by: Mereen-Johnson, SCMI, Cornell, Diehl, Brewer and Yates.

Band Saws by: McDonough, Salem, Filer & Stowell, Wheiland, Brewer, Kimwood, Ferrari, Foster.

UNIT (Gallons)	CATALOG #
CASE (4 Gallons)	BL 9-1
PAIL (5 Gallons)	BL 9-5
DRUM (55 Gallons)	BL 9-55



Smith Sawmill Service

181 County Road 4763
Timpson, TX 75975 USA

Phone: 1-800-598-6344

Fax: 936-354-3975

sawmill.shop

info@smithsawmillservice.com

