



# Machine jack model MH

## Capacity 5 - 25 t

For lifting heavy machinery and other loads.

#### **Features**

- Can be used in every position.
- Lifting by means of a hand pump.
- Lowering by means of a precision lowering valve.
- With carrying handle for models MH 50 and MH 100.
- With carriage for model MH 250.
- Pressure control valve for a longer service life of the jack.
- Integrated lifting limitation.
- Low application height of the claw.
- Slewing claw (models MH 50 and MH 100)
- Large base plate for a high level of stability.
- Stable construction with hard-chromium plated piston rod.



### Technical data model MH

Model	EAN-No. 4025092*	Capacity	Lift	Application height min. with claw	Application height min. with head	Pump lever force with full load	Weight
	4050939***	t	mm	mm	mm	daN	kg
MH 50	*983815	5	205	25	≤368	38	25
MH 100	*983730	10	230	30	≤420	40	35
MH 250	***005269	25	215	58	≤505	40	109

## Dimensions model MH

Model	MH 50	MH 100	MH 250
A, mm	393	449	-
B, mm	320	325	459
C, mm	213	205	420
D, mm	115	120	220
E, mm	53	55	90
G, mm	25	30	58
H, mm	368	420	505
H1, mm	573	650	720
H2, mm	205	230	215
J, mm	77	74,5	142,5
K, mm	93	108	175
L, mm	520	520	920/840
M, mm	740	745	1305/1225
N, mm	140	170	210/283
Ø Z, mm	76	91	155





