

## Tiger Recovery Blocks Model No. TRE

### Main Features

- Part of the Tigersafe range of height safety equipment
- Lightweight, compact and durable
- Triple pawl brake system with energy dissipating mechanism
- Side cable exit for smooth operation and reduced cable wear
- Ergonomic carrying handle makes transport, set-up and storage easy and safe
- 150kg capacity for operator and tools
- Top anchor point with built-in swivel - limits lifeline twisting
- Supplied with screw gate karabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- All fittings meet EN 362:2004
- Available with 15m or 30m wire rope lengths
- Complete with energy absorber
- Buffer spring at cable exit protects block and allows for smooth operation
- Easy to inspect
- Fully serviceable by an approved Service Agent/Centre
- High strength ABS (thermoplastic) casing
- Side case with metal bush for shaft housing
- Minimum static strength 12kN
- 4.8mm galvanised wire rope
- Supplied with pull down cord
- Conforms to EN 360:2002 and BS EN 1496:2017 Class B
- PPE Regulation (EU)2016/425
- SATRA Certified



The Tiger Recovery Winch functions as a standard fall arrest block, but in the event of a fall, the rewind/rescue mechanism can be engaged to raise and/or lower a fallen worker. They can be mounted onto a tripod or a davit arm for access and egress from a confined space.

### Certification:

Each item comes fully certified with a test certificate or an EC Declaration of Conformity. The above items are in conformity with the provisions of Council Directive 89/686/EEC and the standards indicated above.

### Technical Data

| Model/Product Code | Length of wire (m) | Net weight (kg) |
|--------------------|--------------------|-----------------|
| TRE-15             | 15                 | 11.8            |
| TRE-30             | 30                 | 18.6            |



Triple pawl brake system

- Maximum rated load: 150kg
- Minimum static strength 12kN
- Braking force: less than 6kN
- Wire Rope - 4.8mm galvanised
- Operating Temperature: -30°C to +50°C
- PPE Category III Retractable Type Fall Arrestor



### Technical Data

| Product Code | Dimensions |     |      |     |
|--------------|------------|-----|------|-----|
|              | A          | B   | C    | D   |
| TRE 15       | 293        | 397 | 975  | 176 |
| TRE 30       | 340        | 477 | 1015 | 200 |



Double boxed packaging

**Our innovation, your safety**