



Tiger Industrial Winch Model No. SF-2200

Main Features

- 2200lb/1000kg lifting & 4400lb/2000kg pulling capacity
- Ratchet handle permits reciprocating handle movement in both directions for lifting and lowering loads
- Positive load-actuated brake can hold the load in any position
- Gears and brake are fully covered to prevent dust, dirt and rain contamination
- Very low operator effort is required for easy operation
- Ratchet handle accommodates installation in cramped locations
- Operating temperature -40°C to +80°C (temperature range of -60°C to +80°C available as an option)

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC.

Technical Data

| Product Code | Pulling Capacity (lbs/kg) | Lifting capacity (lbs/kg) | Hand Force Required (kg) | Gear Ratio | Hub Diameter (mm) | Handle Length (mm) | Unit Weight (with handle) (kg) | Cable Diameter (mm/inch) | Cable Storage Cap. (m) | |
|--------------|---------------------------------|---------------------------------|--------------------------------|---------------|-------------------------|--------------------------|--------------------------------|--------------------------|------------------------------|--|
| SF-2200 | 4400/2000 | 2200/1000 | 10 | 22 2.1 | ø80 | 300 | 17 5 | a8 0/a5/16 | 32 | |

