

Tiger Fall Arrest Blocks (Wire)

Model No. TIB

Main Features

- Part of the Tigersafe range of height safety equipment
- Lightweight, compact and durable
- Triple pawl brake system with energy dissipating mechanism
- Side cable exit for smooth operation and reduced cable wear
- Ergonomic carrying handle makes transport, set-up and storage easy and safe
- 150kg capacity for operator and tools
- Top anchor point with built-in swivel - limits lifeline twisting
- Supplied with screw gate karabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- All fittings meet EN 362:2004
- Available with 6m, 10m, 15m, 20m, 30m wire rope lengths
- Buffer spring at cable exit protects block and allows for smooth operation
- Easy to inspect
- Fully serviceable by an approved Service Agent/Centre
- Highly durable nylon casing*
- Side case with metal bush for shaft housing
- Minimum static strength 12kN
- 4.8mm galvanised wire rope
- Supplied with pull down cord
- Conforms to EN 360:2002 - EC Notified Body Apave
- PPE Regulation (EU)2016/425



*6m wire metal case option also available –
please see our separate technical information for more details



Tiger TIB Fall Arrest Retractable Lifelines/Inertia Reels (PPE Category III) are designed to reduce vertical impact force on the body caused by falling from height. They are used to provide semi-permanent fall protection. The lifeline tension allows the user to move freely around the work area.

Certification:

Each item comes fully certified with a test certificate or an EC Declaration of Conformity. The above items are in conformity with the provisions of Council Directive 89/686/EEC and the standards indicated above.

Technical Data

Model/Product Code	Length of wire (m)	Net weight (kg)
TIB-06	6	5.9
TIB-10	10	6.5
TIB-15	15	8.0
TIB-20	20	10.8
TIB-30	30	13.3

- Maximum rated load: 150kg
- Minimum static strength 12kN
- Braking force: less than 6kN
- Wire Rope - 4.8mm galvanised
- Operating Temperature: -30°C to +50°C
- PPE Category III Retractable Type Fall Arrestor



TIB-06
TIB-10



TIB-15



TIB-20
TIB-30



Triple pawl brake system



Double boxed packaging



Our innovation, your safety