

# Ride-on Brush Cutter, AR950FA



**High-end model**

**AR950FA**

**(4WD)**



**CE Certified**


# Appearance



**4WD AR950FA**



## Front Suspensions



- ▶ It's the **Industry-First!!**  
Newly equipped Front Suspensions on **the 4WD.**
- ▶ **Comfortable ride**  
Vibration is reduced with the front suspensions.

※Optional part



Bull Bar

## Strong Steel Bumper

- ▶ This bumper knocks down hard bushes.
- ▶ Bull Bar (footrest) optionally can be installed.  
The bull bar also drives over hard bushes.

## F/R Seat Adjustment

- ▶ Depending on the body size, the driver's seat can be adjusted to the F/R by 60 mm.



## Easy step-less adjustment of the cutting height

- ▶ The cutting height adjustment lever is light to operate.

## Round-shaped engine cover

- ▶ **Tree-friendly designed engine cover does not damage tree or fruit.**

## Light Steering Wheel

- ▶ **Even though it is a 4WD, the light steering wheel does not make the driver tired.**

## Lug tire for tough work



- ▶ **Its excellent traction and mud grip tires provide smooth running in difficult conditions such as a slope.**



## Low center of gravity

- ▶ With a low center of gravity, AR950FA ensures stable drive on uneven grounds and delivers great results in narrow, low and bushy spaces.



## Adjustable HST Pedal

- ▶ Adjustable 50mm to the Front
- ▶ Comfortable driving position



**Short turning radius**

# Main Specifications 1 : AR950FA



Model		AR950FA		
Body Dimensions	Overall Length (mm)	1965		
	Overall Width (mm)	1075		
	Overall Height (mm)	955		
	Wheelbase (mm)	1320		
	Tread (mm)	Front Wheel 830	Rear Wheel 785	
Weight (k g)		360		
Cutting System	Cutting Width (mm)	950		
	Cutting Blade Type X Q'ty	Free Knife × 2 pcs		
	Cutting Blade Fixing System	Lock Nut Type		
	Cutting Height (mm)	35~125		
	Power Transmission	V belt (Brake interlock)		
	Max. Working Efficiency	95 (Eco Drive : 85)		
Traveling	Travel Shifting · Drive Wheels		HST(Kanzaki13cc) · 4WD	
	Speed	Forward (km/h)	0~10	
		Reverse (km/h)	0~8.5	
	Wheel	Front	4.00-7-4PR (φ400mm)	
		Rear	17X8.00-8-4PR (φ440mm)	
	Differential Lock		Including	
	Brake		Internal Expanding	
	Min. Turning Radius		2200	
Max. Climbing Ability (degree)		25		

# Main Specifications 2 : AR950FA



Model		AR950FA	
Engine	Engine Model	Kawasaki F S 691V	
	Output / Rotation Speed ( kW{P S} / r p m )	gross. : 17.2{23.4} / 3600 Displacement 726 cm <sup>3</sup>	
	Rotation Speed ( r p m )	Max.	3350
		ECO	3100~3000
		Idling	1550
	Fuel Tank Capacity ( ℓ )		14
Equipment	Upper-Lower Adjustment for Handle ( mm )	0 · 30 (2-steps)	
	Cutting Blade Washing	Including	
	Head Light	Including (LED)	
	Hour Meter	Including	
	Oil Warning Lamp	Including	
	Front Suspension	Including	
	Protection Frame	O P T	
	Bull bar	O P T	
	Snow Blade	None	
	Outlet cut bush in the center	None	
	Towing Hook	Internal	