



## Marine & Commercial Vinyl

### ***Product Specification Sheet***

PROPERTY	SPECIFICATION	TEST METHOD
<b>Product</b>	Marine & Commercial Vinyl	
<b>Application</b>	Hospitality, Contract, Home Office, Automotive, Aftermarket, Residential, Medical	
<b>Normal Weight</b>	567gsm	
<b>Width</b>	137cm	
<b>Roll Length</b>	27m	
<b>Backing</b>	100% Polyester Knit	
<b>Abrasion Resistance</b> (Protected with Blockade™ Topcoat to pass)	250, 000 Cycles Double Rub	Wyzenbeek/CFFA-1 Federal Standard 191A Method 5304
<b>Ultra Violet Resistance</b> (Protected with Blockade™ special finish)	1000 Hours	
<b>Anti-Bacterial</b>		Passes AATCC Test Method 147-1988 Back protected to conform with ASTM G21
<b>Flammability Requirements</b>		Manufactured to meet MVSS302, California Tech Bulletin 117, IMO A.652(16)8.2, NFPA 260
<b>Tensile Strength</b>	11/11 kN/m	ASTM D-751
<b>Tear Strength</b>	27/13.4 N	MF-MH BN 22.1



**BluSky Products Pty Ltd** ABN 71 616 950 371

A: 28 Sunblest Crescent Mount Druitt NSW 2770 Australia

P: +61 2 98320848 F: +61 2 98320843 E: info@bluskyproducts.com.au

[www.bluskyproducts.com.au](http://www.bluskyproducts.com.au)