

SATAjet® 5000 B

RP® /HVLP



Technical data:	RP	HVLP
Inlet pressure	Operating range (Field of application): 7 psi - 29 psi Compliant: max. 29 psi	Operating range (Field of application): 7 psi - 29 psi Compliant: max. 29 psi
Air consumption at 29 psi	10.2 CFM	15.2 CFM
Spray distance	Operating range (Field of application): 3.9 in - 8.3 in Recommended: 6.7 in - 8.3 in	Operating range (Field of application): 3.9 in - 8.3 in Recommended: 3.9 in - 5.9 in



1,0	1,1	1,2	1,2 W	WSB	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,2	2,5
-----	-----	-----	-------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Standard with RPS multi-purpose cup 0.3 l / 6 l / 0.9 l (each 1x) with swivel joint

RP	-	215640	209858	209866	-	209874	209882	-	209890	-	209908	-	209916	-	-
HVLP	210732	-	210740	-	210757	210765	210799	210823	-	210831	-	-	-	210856	-

Nozzle set

RP	210245	210252	210260	210278	-	210286	210294	-	210302	-	210310	-	210328	-	210336
HVLP	210955	-	210963	-	210971	210989	211011	211045	-	211052	-	211060	-	211078	-

Test Air Cap

RP	215962	-	215962	215970	-	215970	-	215970	-	-	-	-	-	-	-
HVLP	215988	-	215996	-	215988	215996	215988	215988	-	-	-	-	-	-	-