



FEATURES

- * 4.3" Touch Screen
- * Waterproof, Dustproof, Anti-Shock
- * SOC Compatible

Standard Package Includes:

Splicer, Power Cord, Stripper, AC Adapter, Battery, SOC Holder, SOC Heater Block, Cooling Tray, Electrode Set, Shoulder Strap, USB Cable, User Manual, Hard Carrying Case.

ORDERING INFORMATION

OFS-935C	Fusion Splicer Standard Package + Precision Cleaver + Spare Battery + Car Charger + Spare Electrodes
-----------------	--

OFS-935C

Fusion Splicer

The PRO OFS-935C is the perfect splicer for ANY job. This splicer has it all, from the easy-to-use touch screen interface to the rock solid core alignment splicing — all at a price that is thousands less than other comparable brands. With an innovative design and engineered with precise manufacturing technology, the OFS-935C gives users an unmatched experience. Splice with confidence no matter what harsh environmental condition you encounter. The OFS-935C offers SOC capability, providing superior performance with reduced insertion loss and back reflection. The OFS-935C is economical, durable and backed by Precision Rated Optics service and warranty in the United States. The OFS-935C is available in three configurations, and is a perfect addition to any PRO Go-Kit!

SPECIFICATIONS

Splicing Method	Economical & High Performance Core Alignment Splicer
Average Loss	(SM)0.02dB, (MM)0.01dB, (DS)0.04dB, (NZDS)0.04dB, (G.657)0.02dB
Return Loss	>-60dB
Splice Time	9s average SM / SM 7s Quick mode
Electrode Lifespan	>3,500 arcs
Applicable Fiber	SM(ITU-TU.652), MM(ITU-TU.651), DS(ITU-T G.653), NZDS(ITU-T.655), G657A, G657B 0.25mm, 0.9mm, 2.0mm, 2.4mm, 3.0mm, FLAT(Indoor cable)
Cleaved Length	Coating Diameter < 0.25mm ~ 8-16mm, Coating Diameter > 0.25mm = 16mm minimum
Coating Diameter	100~1,000 um
Cladding Diameter	80~150um
Heating Programs	Factory installed mode: 9, User Installable mode: 23
Heating Time	Typical 18s
Protection Sleeve	40mm, 60mm, SOC Connector
Data Output	HDMI
Splice Programs	Factory Installed Mode: 33, User Installable Mode: 70+
Splice Memory	Up to 2,000 Records and 2,000 Splice Images
Battery	Typical 200 Cycles (Splice & Heat) / Single Battery
Power Supply	AC 100-240V Input or DC9-14V
Monitor	Color 4.3" LCD Monitor, with Touch Screen (Tempered Glass)
Cameras	2 CCD Camera System
Magnification	XY style: 150 Power, X/Y: 300 Power
Fiber Display	X / Y or XY, Single X.Y
Size/Weight (WxDxH)	5.47" x 4.84" x 5.11" / 3.06lb (139 x 123 x 130mm / 1.39Kg w/o Battery)
Operating Environment	Elevation: 0-5,000 Meters, Temp: -40~176°F (-40~80°C), 0-95% Relative Humidity
Wind Protection	The Max Wind Speed 15m/s
Storage Conditions	Temp: -40~176°F (-40~80°C), 0-95% Relative Humidity, Battery: -4~86°F (-20-30°C)
Pull Test	1.96~2.25N (Standard)
Warranty	Standard 1-Year Manufacturer Warranty

