



The PRO OFT-1000 Smart OTDR is a new generation of portable and intelligent measuring instruments. It features a 3.5-inch color LCD screen. The internal integration can help customers effectively troubleshoot problems in the field when testing or performing maintenance. The PRO OFT-1000 OTDR measures the length, loss, and connection quality of all kinds of optical fiber cables. It can also be used in engineering construction, line maintenance & testing, emergency repair, and the development and production of optical fiber cables.

FEATURES

- * Lightweight, portable and cost-effective
- * One key operation with test data results
- * Integrated with VFL, optical power meter, laser source, and RJ45 cable length test function
- * Dustproof, waterproof, and shockproof
- * High-capacity battery for extended operation time
- * Installation and maintenance fault location of FTTX and access network

Standard Package Includes:

Smart OTDR, FC Adapter, SC Adapter, Universal Adapter, RJ-45 Toner, Charging Cable, Soft Carry Pouch

ORDERING INFORMATION

OFT-1000	OFT-1000 Smart OTDR (1310/1550) SM
----------	------------------------------------

OFT-1000

Smart OTDR (1310/1550)

The PRO OFT-1000 Smart OTDR is a new generation of portable and intelligent measuring instruments. It features a 3.5-inch color LCD screen. The internal integration can help customers effectively troubleshoot problems in the field when testing or performing maintenance. The PRO OFT-1000 OTDR measures the length, loss, and connection quality of all kinds of optical fiber cables. It can also be used in engineering construction, line maintenance & testing, emergency repair, and the development and production of optical fiber cables.

SPECIFICATIONS: GENERAL

Display	3.5-inch, Color Non-Touch LCD
Power Supply	3.7V, 4000mAh; Adapter 5V DC, 2A
Lithium battery	Battery Duration Standby: >20h; Measuring Time >12h
Data Storage	Internal ≥600; External: TF Card (not included)
Operating Condition	0~95% relative humidity, 14~122°F (-10~50°C)
Storage Condition	0~95% relative humidity, -40~158°F (-40~70°C)
Size/Weight (WxDxH)	6.81 x 3.23 x 1.46in / 12.35oz (173 x 82 x 37mm / 350g)

SPECIFICATIONS: OTDR

Wavelength:	1310/1550 ± 20nm (SM)
Dynamic Range:	24dB/22dB
Optical Connector:	FC/SC
Event Dead Zone:	3m
Attenuation Dead Zone:	8m
Measuring Range:	500m~60km
Pulse Width:	3ns~10us
Accuracy Distance (Reflection Event):	± (1m + Sampling Interval + 0.005% x Test Distance)
Loss Accuracy:	± 0.05dB/dB
Sampling Points:	16K~128K
Sampling Resolution:	0.05m~8m
Reflection Accuracy:	± 3dB
Adapter:	FC/SC



OFT-1000

Smart OTDR (continued)

SPECIFICATIONS: POWER METER

Measurement Range	-50~+26dBm
Wavelength	800nm~1700nm
Calibrated Wavelength	850nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm
Detector	InGaAs
Uncertainty:	< ±5%
Frequency Identification	CW/270Hz/300Hz/1KHz/2KHz
Adapter	FC/SC

SPECIFICATIONS: LASER SOURCE

Wavelength	1310/1550nm
Fiber Type	SM
Emitter	FP-LD
Adapter	FC/SC
Output Power	≥ -5dBm
Output Stability:	CW, ±0.5dB/15min(test after 15 minutes of preheating)
Modulation Frequency	CW/270Hz/330Hz/1KHz/2KHz

SPECIFICATIONS: VFL

Wavelength	650nm ± 20nm
VFL Output Power	≥ 10mW
Mode	CW/1Hz/2Hz
Fiber Type	SM/MM
Adapter	2.5mm Universal

SPECIFICATIONS: RJ-45 TONER

Cable Receiver	Will be supplied with accessories
Test Range	300m



PRECISION RATED OPTICS IS THE IN-HOUSE BRAND OF FIBEROPTICS.COM AND BOTH ARE PART OF THE ADTELL GROUP.

