

Keystone B-Vent Fireplaces Premium (BVP42) and Deluxe (BVD34 & BVD36)

Keystone 42 B-Vent Fireplace in a White Profile Mantel trimmed with Black Slat Louvers, Aged Brick Liner and Custom Tile Surround



Keystone Series

Keystone Premium & Deluxe Models

Keystone B-Vent Fireplaces combine modern technology with traditional venting to create the appearance and performance of a conventional fireplace but with the convenience of gas.

Our B-Vent systems let you prolong the flicker of the flames without overheating your room. The BVD34 input is 21,000 Btu; the BVD36 is 25,000 Btu; and the Premium BVP42 is 30,000 Btu.

FBB4 automatic Blower with variable speed control may be used on Louvered models.

Standard Features

- Millivolt and Intermittent Pilot Models
- Louvered and Flush Models
- Natural Gas (LP conversion available)
- Zero Clearance Certified
- Remote Control Options
- A Variety of Decorative Accessories



Keystone hand-painted Ceramic Fiber Log Set (BVD34) on Contour Burner



Keystone 34 Deluxe Flush B-Vent Fireplace




Keystone 42 Premium Flush B-Vent Fireplace shown with optional Ceramic Aged Brick Liner

Options & Accessories

Outer Frames & Bottom Trim

Our metal three-piece outer frames let you transition from your fireplace to any adjoining surface – wooden mantel, tile, stone, or any noncombustible material. Choose from steel frames – with traditional crisp lines – or our new extruded aluminum frames – with a profile that combines gentle concaves with flat surfaces. Each is available in matte black or hammered pewter. Our bottom trim completes the fourth side of the color frame.

Extruded Aluminum Frames



Matte Black (Shown on Cherry Mantel)



Hammered Pewter (Shown on Oak Mantel)

Liners







Smoked Herringbone

Frame with Barrier Screen




Rectangle Door Frame with Barrier Screen

Decorative Doors – *include handles*Requires Rectangle Frame with Barrier Screen



Decorative Door Plain Rectangle

Decorative Louvers – with screens



Bottom Trim



Control Options

Choose from battery-operated or electric remote control, or opt for the simple wall switch.



FWS Wall Switch




FRBC Battery-operated Remote Control

Keystone Fireplace Specifications

Model	A	В	С	D	E	F	G	н	ı	J	Max Weight (lb.)	Input Btu	Vent Size (inches)
Keystone 34	37	34	22 7/8	35 5/8	32 3/4	14 7/8	6 3/8	5 7/8	24 1/2	12 1/4	110	21,000	4
Keystone 36	39	36	24 7/8	37 5/8	34 3/4	18 3/8	6 3/8	8 3/8	22 1/2	11 1/4	121	25,000	6
Keystone 42	43	40	24 7/8	37 5/8	34 3/4	18 3/8	6 3/8	6 3/8	26 1/2	13 1/4	134	30,000	6

Fireplace Specification Dimensions are in inches.



Keystone Fireplace Framing Dimensions

Model	Framing Width	Framing Height	Minimum Framing Depth		
Keystone 34	37 3/8	35 3/4	14 3/8		
Keystone 36	39 3/8	37 3/4	17 7/8		
Keystone 42	43 3/8	37 3/4	17 7/8		

All Framing Dimensions are in inches.

Keystone Mantels - See Profile Mantels and Mantelshelves

For most installations, this B-Vent fireplace will be framed in behind a wall or in a chase.

Gas Inlet for Fireplace Models			
Type of Gas	Natural (LP conversion kit available)		
Iron Pipe Size (N.P.T.)	1/2-inch		
Ignition System	Standing Pilot/Piezo or Intermittent Pilot		

Warranty All parts carry a 3-year limited warranty. All remote controls carry a 1-year limited warranty.

Empire is committed to continuous product improvement; specifications are subject to change without notice. Dimensions in this brochure are approximate; read and follow the framing dimensions in the owners manual supplied with your Empire product. Flame size, shape, and color will vary from photos.

This appliance is design-certified to the ANSI standard by:

Member of the following industry associations:

















Empire Comfort Systems Inc. 918 Freeburg Ave. Belleville, IL 62220-2623 info@empirecomfort.com

WMH-00702 3/15/19

The Empire Comfort Systems and White Mountain Hearth names and logos are registered U.S. trademarks