

# SAFETY DATA SHEET

# SECTION 1. Identification of the Substance and Manufacturer

Product: 13600 Cupric Oxide

Copper (II) Oxide

Common uses: Industrial Chemicals.

Restrictions of use: None known.

Manufacturer: American Chemet Corporation www.chemet.com

145 HWY 282 / P.O. Box 1160

East Helena, MT 59635 U.S.A.

+1(406) 227-5302 (Phone) +1(406) 227-8047 (Fax)

24-Hour Emergency: Verisk 3E

American Chemet Corporation/Verisk 3E Global Incident Response Access Code: 334129

American Chemet Corporation/Verisk 3E Contract Number 14862

Americas	Europe	Asia Pacific	Middle East/Africa
1-866-519-4752 (US, Canada, Mexico) or 1-760-476-3962	1-760-476-3961	1-760-476-3960	1-760-476-3959

Local Contact (if Applicable):

### SECTION 2. Hazard Identification

#### **Classification System:**

The classification is based on the criteria in the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### **GHS Label Elements**



#### Warning

H410 - Very toxic to aquatic life with long lasting effects. Aquatic Acute, Category 1. Aquatic Chronic, Category 1.



H313 - May be harmful in contact with skin, Category 5.

H332 - Harmful if inhaled, Category 4.

H320 - Causes eye irritation, Category 2B.

### **Precautionary Statements:**

P264 - Wash thoroughly after handling.

P363 - Wash contaminated clothing before reuse.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P337 + P313 - If eye irritation persists gets medical advice/attention.

P261 - Avoid breathing dust/mist.

P271 - Use only outdoors or in a well ventilated area.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison control center or doctor.

P312 - Call a poison control center or doctor if you feel unwell.

P273 - Avoid release to the environment.

P391 - Collect spillage.

P501 - Dispose of contents/container in accordance with local/national/international regulations.

## SECTION 3. Composition/Information of Ingredients

 Ingredient
 %
 EC Number
 CAS No.

 Cupric Oxide
 98%
 215-269-1
 1317-38-0

 Cuprous Oxide
 1.5%
 215-270-7
 1317-39-1

SECTION 4. First Aid Measures

> Inhalation: Remove to fresh air. Lay patient down. Cover with blanket. Ingestion: Give 200-300 mL water to drink. DO NOT induce vomiting.

Skin Contact: For skin exposure, remove contaminated clothing and wash with soap and water. If irritated, flush eyes and skin with large volumes of fresh water for 15 minutes. Eye Contact:

Medical Notes: If any adverse symptoms persist seek immediate medical attention.

Most important symptoms and effects, both acute and delayed. Dust may have irritant effect on skin, eyes and air passages.

Indication of the immediate medical attention and special treatment

Treat symptomatically as described above in this section.

needed.

**SECTION 5.** Fire-Fighting Measures

Extinguishing Media: CO<sub>2</sub>, ABC extinguisher, or water spray.

Special Fire Fighting Procedures: Material is non-flammable. Use firefighting measures appropriate to surrounding

materials.

Special Exposure Hazards: Cuprous oxide is stable in dry air, but can oxidize to cupric oxide in the presence of moist

air at temperatures above 100°C.

Additional Information: Collect contaminated fire fighting water separately.

It must not enter the sewer system.

Personal Protective Equipment: Wear self-contained breathing apparatus.

SECTION 6. Accidental Release Measures

Personal Precautions: Spilled material may produce dust hazard if not handled correctly. Wear appropriate

personal protective equipment: coveralls, gloves & eye protection.

Do not allow to enter drains or watercourses. If the product enters drains or sewers, **Environmental Precautions:** 

immediately inform the local water company. Where there is contamination of streams,

rivers or lakes, contact local agency with responsibility for the environment.

Methods for Clean Up: Contain spillages and clean up with vacuum or conventional tools and attempt to

minimize dusting. Place in a suitable container for recycling or disposal in accordance

with local and national waste regulations.

SECTION 7. Handling and Storage

> Handling: Only use in a well-ventilated area and prevent the creation of dusts. If concentrations exceed the

> > occupational exposure limits, use suitable respiratory protection.

Store in a cool, dry, well-ventilated place. Keep away from food and drink. Storage:

> Keep containers sealed. Industrial chemicals

Common uses: **SECTION 8.** Exposure Controls/Personal Protection

> Occupational Exposure Standards: Copper as dusts & mist:

OSHA PEL & ACGIH TLV 1 mg/m<sup>3</sup> 8-hour TWA

Occupational Exposure Controls: All personal protective equipment, including respiratory equipment, used to

control exposure to hazardous substances must be selected to meet the

requirements of national personal protective equipment regulations.

Personal Protection:

To keep below the U.S.A. OSHA and EU exposure limits, use general dilution type Ventilation:

ventilation.

Respiratory Protection: Cartridge type particulate filter respirator or dust-mask conforming to U.S.A. NIOSH.

Refer to Respiratory Protective Devices approved by NIOSH under 42 CFR 84 and

the appropriate European standard.

Hand Protection: Wear if skin contact is probable and skin is sensitive.

Eye Protection: Safety glasses or goggles.

Long sleeve shirt(s) if contact is probable and skin is sensitive. Skin Protection:

**Environmental Protection:** Do not allow to enter drains or watercourses.

**SECTION 9.** Physical and Chemical Properties

> **Appearance** Powder. Colour Black Odour Odourless. Odour Threshold (ppm) Not applicable.

pH (Value) Not applicable. (inorganic solid).

Melting Point (°C) 1326°C.

Not applicable. (solid that melts >300 °C) Boiling point/boiling range (°C):

Flash Point (°C)

Evaporation rate

Not applicable. (inorganic solid).

Not applicable. (inorganic solid).

Flammability (solid, gas)

Flammable Limits (Upper) (%v/v)

Non-flammable.

Not applicable.

Vapour Pressure (Pascal) Not applicable. (inorganic solid Melting Point

(1326°C)).

Vapour Density (Air=1)

Not applicable. (inorganic solid).

Relative Density

6.32 g/cm³ at 20°C

Relative Density 6.32 g/cm³ at 20°C

Solubility (Water) >0.230 g/l at 20°C (pH 5.1– 5.5) 0.000394 g/l at 20°C (pH 6)

0.00001 g/l at 20°C (pH 9)

Specific Gravity (Water = 1) 6.4

Partition Coefficient (n-Octanol/water)

Not applicable. (inorganic solid).

Auto Ignition Temperature (°C) None

Decomposition Temperature (°C) >300°C at 101.72 kPa

Viscosity (mPa.s) Not applicable (inorganic solid)

Explosive properties Not explosive.
Oxidising properties Not oxidising.

Percent Volatile by volume (%) 0%
Other information None

### CTION 10. Stability and Reactivity

Reactivity Thermally stable.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions Will not occur.

Conditions to avoid Keep at a temperature not exceeding (°C): 100 (in

moist conditions)
Avoid dust generation.

Incompatible Materials May react violently with: Acids, Bases.

Hazardous Decomposition Product(s)

Copper fumes will be released if heated above its

melting point (1326 °C).

### SECTION 11. Toxicological Information

**Acute Toxicity** 

Oral (Rat): Not classified Skin Irritation: Not classified as a skin irritant Eye Irritation: Effects reverse within 7 days. Inhalation (Rat): Dust  $LC_{50} \le 5000$  mg/kg Eye Irritation: Sensitization: Not classified as a dermal sensitizer

Mutagenicity, Carcinogenicity, Reproductive Toxicity Based upon the available data, the classification criteria are not met.

#### SECTION 12. Ecological Information

Toxic to fish and other aquatic organisms.

Prevent from entering drains, sewers, and surface water.

### SECTION 13. Disposal Considerations

PACKAGING: Dispose of in accordance with procedures applying to the disposal of the product.

PRODUCT: Dispose of surplus and contaminated materials (including sawdust) at an approved landfill or in

accordance with other national or regional provisions.

#### SECTION 14. Transportation Information

US DOT: Not Regulated. Class 9 materials do not require placarding for U.S.A. ground transport (49 CFR

172.504(f)(9)). *Exceptions*, except when all or part of the transportation is by vessel, the requirements specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car, or aircraft (49 CFR 171.4(c)). Permissive labelling is allowed by U.S.A.

DOT (49 CFR 172.401(c)).

Proper Shipping Name: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Copper (II) Oxide), Class 9, PG III, MARINE POLLUTANT

# . Land transport ADR/RID (cross-border) Excluding U.S.A. Ground Transport





· ADR/RID class: 9 (M7) Miscellaneous dangerous substances and articles

Danger code (Kemler): 90
UN Number: 3077
Packaging group: |||
Hazard label: 9

· Proper shipping name: 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Copper (II) Oxide)

· Tunnel Restriction Code: E

· Maritime transport IMDG:





·IMDG Class:
· UN Number:
· Hazard Label:
· Packaging group:
· Marine pollutant:
yes

Proper shipping name: 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Copper (II) Oxide)

• EmS Code: F-A, S-F

· Air transport ICAO-TI and IATA-DGR:





· ICAO/IATA Class: 9
· UN/ID Number: 3077
· Hazard Label: 9
· Packaging group: ||||

· Proper shipping name: 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Copper (II) Oxide)

### SECTION 15. Regulatory Information

U.S. EPA EPCRA Section 313 Reportable Product – (contains copper)

U.S. EPA Reportable Quantity: 5,000 lbs. (2,270 kg)

REACH Registration Number for American Chemet Corporation's Cupric Oxide: 05-2114625702-54-0000

#### SECTION 16. Other Information

Keep out of reach of children. Read and follow all label instructions. This information is based on our present knowledge. However, this is not a guarantee of specific product features. It is the user's responsibility to satisfy themselves as to the suitability and completeness of this information for their own particular use.

Country Specific 24-Hour Emergency Phone Numbers: Verisk 3E

Country	Number	Languages
Australia	+61 1 800 686 951	English
China	+86 4001 2001 74	Chinese
New Zealand	+64 800 451719	English
United Kingdom	+44 8 08 189 0979	English
Korea	+82 070 4732 5813	Korean

Date of Last Revision: 2/25/19