

Univar USA Inc Safety Data Sheet

3075 Highland Pkwy, Ste 200, Downers Grove, IL 60515 (425) 889 3400

Emergency Assistance

For emergency assistance involving chemicals call Chemtrec - (800) 424-9300

Ref: 02-3-2-25-000



FETY <u>DATA SHEET</u>

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

N® Sodium Silicate Solution Product Name

Alternative names Sodium silicate solution

(2.6 < MR < = 3.2)

CAS No. 1344-09-8 EINECS No. 215-687-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) General purpose industrial chemical for use in a wide range of

applications.

Binding agent : Corrosion inhibitor : Dust binding agent : Flame retardant or fire preventing agent; Flotation agent; Stabiliser;

Viscosity control agent

Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

PQ Corporation Company Identification

P.O. Box 840 Valley Forge PA 19482 USA

+1 610-651-4200

Telephone: E-Mail (competent person) sds.uk@pqcorp.com

1.4 Emergency telephone number

Emergency Phone No. +1 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification Skin Irrit. 2 Eye Irrit. 2

Hazards summary Alkaline.

Irritating to eyes and skin. Spilled material is slippery

2.2 Label elements

Hazard pictogram(s)



Signal word(s) Warning

H315: Causes skin irritation. Hazard statement(s)

H319: Causes serious eye irritation.

Revision: GHS v1 Date of Issue: 02/2015

PQUS - GHS - 3 Date Previous Issue: 1/17/2013 Page: 1 of 6

- en -





Precautionary statement(s) P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

2.3 Other hazards Dries to form glass film which can easily cut skin. Can etch glass

if not promptly removed.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Regulation (EC) No. 1272/2008 (CLP)

Ingredient(s)	%W/W	CAS No.	EINECS No. /	Hazard symbol(s) and
			REACH Registration	hazard statement(s)
Silicic acid, sodium salt	37.5	1344-09-8	215-687-4	H315 : Skin Irrit. 2 ;
				H319 : Eye Irrit. 2
Water	62.5	7732-18-5	231-791-2	-

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids

apart, for at least 15 minutes. Obtain immediate medical

attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop,

obtain medical attention.

Inhalation Remove patient from exposure, keep warm and at rest. Obtain

medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water and give

200-300 ml (half a pint) of water to drink. Obtain medical

attention.

4.2 Most important symptoms and effects, both acute and

delayed
4.3 Indication of any immediate

medical attention and special

treatment needed

Alkaline.

Irritating to eyes and skin. The toxicity of sodium silicate is

dependent on the silica to alkali ratio and on the pH.

Obtain immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media
Unsuitable extinguishing Media

Compatible with all standard fire fighting techniques.

None known.

5.2 Special hazards arising from

Not applicable. Aqueous solution. Non-combustible.

the substance or mixture

5.3 Advice for fire-fighters None.

no navioo ioi mo ngittoro

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Wear eye/face protection.

Revision: GHS v1 - en - Ref: 02-3-2-25-000
Date of Issue : 02/2015 PQUS - GHS - 3
Date Previous Issue : 1/17/2013 Page: 2 of 6





6.2 Environmental precautions Do not allow to enter drains, sewers or watercourses. Advise

Authorities if spillage has entered water course or sewer or has

contaminated soil or vegetation.

6.3 Methods and materials for containment and cleaning up

Caution - spillages may be slippery. Contain spillages with sand, earth or any suitable adsorbent material. Transfer to a container

for disposal or recovery.

6.4 Reference to other sections See Also Section 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with eyes, skin and clothing.

Avoid generation of mist. Provide adequate ventilation. Emergency shower and eye wash facilities should be readily

available.

See Also Section 8

7.2 Conditions for safe storage, including any incompatibilities

Storage temperature 0-95° C. Loading temperature 45-95 ° C.

Do not allow material to freeze. Provide an adequate bund wall. Unsuitable containers: Aluminium

See Also Section 10.

7.3 Specific end use(s) See also Annex to the extended Safety Data Sheet.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

SUBSTANCE.	Occupational Exposure Limits		
Silicic acid, sodium salt	No Occupational Exposure Limit assigned.		
	An exposure limit of 2 mg/m3 (15 min TWA) is recommended by analogy		
	with sodium hydroxide (UK EH40).		

8.2 Exposure controlsWear protective equipment to comply with good occupational

hygiene practice. Do not eat, drink or smoke at the work place.

8.2.1 Appropriate engineering controls

hygiene practice. Do not eat, drink or smoke at the work place.

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure,

mechanical ventilation (dilution and local exhaust), and control of

process conditions.

8.2.2 Personal Protection

Respiratory protection Respiratory protection not normally required. Advice on

respiratory protective equipment is given in the HSE (Health and

Safety Executive) publication HS(G)53.

Eye/face protection Chemical goggles (EN 166).

Skin protection Wear suitable protective clothing and gloves. Plastic or rubber

gloves. For example EN374-3, level 6 breakthrough time

(>480min). Wear suitable overalls.

8.2.3 Environmental Exposure

Controls

The primary hazard of sodium silicate is the alkalinity. Avoid

release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Liquid. Almost colourless.

Odour Odourless.
Odour Threshold (ppm) Not applicable.
pH (Value) Alkaline. 11-12
Freezing Point (°C) Not applicable.
Melting Point (°C) Not applicable.

Boiling Point (°C) 100

Flash Point (°C) [Closed cup] Not applicable.

Revision: GHS v1 - en - Ref: 02-3-2-25-000

Date of Issue: 02/2015 PQUS - GHS - 3

Date Previous Issue: 1/17/2013 Page: 3 of 6





Evaporation rate Not applicable. Flammability (solid, gas) Not applicable. **Explosive Limit Ranges** Not applicable. Vapour Pressure (mm Hg) Not applicable. Vapour Density (Air=1) No data.

Density (g/ml) 1.41 g/cm3 (20°C), 42.0° Bé, 11.75 lbs/gal

Solubility (Water) Soluble. Solubility (Other) No data. Partition Coefficient No data. Auto Ignition Point (°C) Not applicable. Decomposition Temperature (°C) Not applicable. Viscosity (mPa. s) Not applicable. Explosive properties Not applicable. Oxidising Properties Not applicable. 9.2 Other information No data.

SECTION 10: STABILITY AND REACTIVITY

See Section: 10.3 10.1 Reactivity

10.2 Chemical stability Stable.

10.3 Possibility of hazardous

reactions

When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon

monoxide.

10.4 Conditions to avoid See Section: 10.3 See Section: 10.3 10.5 Incompatible materials 10.6 Hazardous decomposition None known.

product(s)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion All symptoms of acute toxicity are due to high alkalinity. Material

will cause irritation. Oral LD50 (rat) 3400 mg/kg bw

Mist is irritant to the respiratory tract. All symptoms of acute Inhalation

> toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m³ Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw

Skin Contact Material will cause irritation. **Eve Contact**

Skin corrosion/irritation Irritating to skin. Irritating to eyes. Serious eye damage/irritation Not sensitising. Sensitisation

Mutagenicity No evidence of genotoxicity. In vitro/in vivo negative.

Carcinogenicity No structural alerts. IARC, NTP, OSHA, ACGIH do not list this

product as known or suspected carcinogen.

Reproductive toxicity No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure Not classified

STOT - repeated exposure Not classified. NOAEL oral (rat) >159 mg/kg bw/d

Not classified **Aspiration hazard**

Other information

SECTION 12: ECOLOGICAL INFORMATION

Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l 12.1 Toxicity

Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700

mg/l

Revision: GHS v1 Ref: 02-3-2-25-000 - en -PQUS - GHS - 3 Date of Issue: 02/2015 Date Previous Issue: 1/17/2013

Page: 4 of 6





12.2 Persistence and Inorganic. Soluble silicates, upon dilution, rapidly depolymerise degradability into molecular species indistinguishable from natural dissolved

silica.

12.3 Bioaccumulative potential Inorganic. The substance has no potential for bioaccumulation.

12.4 Mobility in soil Not applicable.

12.5 Results of PBT and vPvB Not classified as PBT or vPvB.

assessment

12.6 Other adverse effects The alkalinity of this material will have a local effect on

ecosystems sensitive to changes in pH.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Dispose of this material and its container to hazardous or special

waste collection point.

Disposal should be in accordance with local, state or national

legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number Not classified according to the United Nations

'Recommendations on the Transport of Dangerous Goods'. Not classified as hazardous under DOT or US Transport

Recommendations.

International Maritime Dangerous Goods (IMDG) Code: Not

classified as hazardous

14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
Not applicable.
Not applicable.
Not applicable.

14.5 Environmental hazards
 14.6 Special precautions for user
 14.7 Transport in bulk according
 Not classified as a Marine Pollutant.
 Unsuitable containers: Aluminium
 Not applicable.

to Annex II of MARPOL73/78 and

to Annex II of MARPOL/3//8 and

the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Inventory Status: Reported/Included. AICS Inventory Status: Reported/Included.

DSL/NDSL Inventory Status: Reported/Included. SARA TITLE III: Not an Extremely Hazardous Substance under §302. Not a Toxic Chemical under §313. Hazard

Categories under §§311/312: Acute

German Water Hazard Classification VwVwS: Product ID number 1314, WGK class 1 (low hazard to water).

HMIS (Hazardous Material Information System) 2,0,0

15.2 Chemical Safety Assessment Information available on request.

SECTION 16: OTHER INFORMATION

Data referenced in this eSDS is from company-owned information and from data legitimately accessed by PQ Corporation through membership of Industry Consortia or other agreements. This includes data relating to toxicology, ecotoxicology, DNELs, PNECs and other information in this eSDS and its annex.

Revision: GHS v1 - en - Ref: 02-3-2-25-000
Date of Issue : 02/2015 - en - PQUS - GHS - 3

Date of Issue : 02/2015 PQUS - GHS - 3
Date Previous Issue : 1/17/2013 Page: 5 of 6





This SDS was last reviewed: 02/2015

The following sections contain revisions or new statements: All sections.

GHS Classification

Signal word(s)
Hazard pictogram(s)

Skin Irrit. 2 Eye Irrit. 2 Warning



Hazard statement(s)

Precautionary statement(s)

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. PQ Corporation gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. PQ Corporation accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

- en -

Revision: GHS v1 Date of Issue : 02/2015

Date Previous Issue : 1/17/2013

Ref: 02-3-2-25-000 PQUS - GHS - 3

Page: 6 of 6

Univar USA Inc Safety Data Sheet

For Additional Information contact SDS Coordinator during business hours, Pacific time: (425) 889-3400

Notice

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process