

CHEMISTRY DILUTION RATIO CHART

- 1) Add to empty tank chemistry as shown in the chart below.
- 2) Fill the tank with hot tap water
- 3) Run the ultrasonic r for several minutes to meld the solution and degas (take out air) the water/solution

Model	TANK CAPACITY			CHEMISTRY IN MILLILITERS FOR DILUTION RATIO		
	US Gal	Litres	Millilitres	10/1 = 10%	20/1 = 5%	30/1 = 3.3%
B1510	0.5	1.9	1900	173	90	61
B2510	0.75	3	3000	273	143	97
B3510	1.6	6.2	6200	564	295	200
B5510	2.5	10.7	10700	973	510	345
B8510	5.5	21.1	21100	1918	1005	681
SM15	0.8	3	3000	273	143	97
SM25	1.4	5.1	5100	464	243	165
SM35	1.6	6.2	6200	564	295	200
SM55	2.8	10.7	10700	973	510	345
SM65	3.8	14.3	14300	1300	681	461
SM85	5.5	21.1	21000	1909	1000	677

Crystal Electronics Inc

WWW.Crystalelectronics.ca WWW.Crystalelectronics.info

2-1251 Gorham St. Newmarket, ON L3Y 8Y6

1 866-669-9728 TOLL FREE