

**Table 2.1.1.3.C**  
**ZONE 2 - Compliance Packages for Electric Space Heating**  
 Forming Part of Sentence 2.1.1.3.(3)

Component	Compliance Package A
Ceiling with Attic Space Minimum RSI (R)-Value <sup>(1)</sup>	8.81 (R50)
Ceiling Without Attic Space Minimum RSI (R)-Value <sup>(1)</sup>	5.46 (R31)
Exposed Floor Minimum RSI (R)-Value <sup>(1)</sup>	5.46 (R31)
Walls Above Grade Minimum RSI (R)-Value <sup>(1)</sup>	5.11 (R29)
<i>Basement Walls</i> Minimum RSI (R)-Value <sup>(1)</sup>	3.52 (R20)
Below Grade Slab Entire Surface > 600 mm Below Grade Minimum RSI (R)-Value <sup>(1)</sup>	0.88 (R5)
Edge of Below Grade Slab ≤ 600 mm Below Grade Minimum RSI (R)-Value <sup>(1)</sup>	1.76 (R10)
Heated Slab or Slab ≤ 600 mm Below Grade Minimum RSI (R)-Value <sup>(1)</sup>	1.76 (R10)
Windows and Sliding Glass Doors Maximum U-Value <sup>(2)</sup>	1.6
Skylights Maximum U-Value <sup>(2)</sup>	2.8
Space Heating Equipment Minimum AFUE	—
HRV Minimum Efficiency	75%
Domestic Hot Water Heater Minimum EF	—
Column 1	2

**Notes to Table 2.1.1.3.C:**

- (1) The values listed are minimum RSI-Values for the thermal insulation component only. RSI-Values are expressed in  $(m^2 \cdot K)/W$ .
- (2) U-Value is the overall coefficient of heat transfer for a window assembly, sliding glass door assembly or skylight assembly expressed in  $W/(m^2 \cdot K)$ . See exceptions and use of alternative Energy Ratings (ER) in Article 2.1.1.8.