

**1½" O.D. heavy duty stainless steel grab bar with concealed mounting:**

**Product Materials**

**FLANGES:** 3/8" dia. 13 gauge stainless steel.  
**ESCUTCHEONS:** 22 gauge stainless steel. One-piece drawn construction with exposed surfaces in architectural satin finish. Snap over flanges to conceal mounting screws.  
**TUBING:** 1½" O.D. 18 gauge stainless steel, seamless construction with exposed surfaces in architectural satin finish. Bent ends of tubing pass thru the flanges and are welded for maximum strength. Intermediate supports are contour cut and joined by welding to form an integral part of the grab bar. All exposed welds ground and polished to blend. Mandrel bending process maintains uniform bar diameter. Return provides 1½" standard safety clearance between wall and bar.

**Strength**

When properly mounted, all Bradley heavy duty grab bar systems meet or exceed the requirements of ANSI Standard A117.1, the ADA and ABA Accessibility Guidelines for Buildings and Facilities (ADAAG), and the Uniform Federal Accessibility Standard (UFAS). Select dimensions of configurations (-001, -054, -055, -059, and -060) are IAPMO certified to support up to 1000 pounds. (Please see Bradley's web site for more information on all grab bar configurations.)

**Installation**

Verify all rough-in dimensions prior to installation. Secure to wall where adequate in-wall backing exists. Use bar as template to locate mounting holes. Drill holes and set anchors as appropriate. Mount grab bar and secure mounting screws (not included). Snap escutcheons into place. For information on Bradley grab bar mounting kits, please visit [bradleycorp.com](http://bradleycorp.com).

**Optional Features**

| Features  | Suffix |
|---|--------|
| <input type="checkbox"/> Safety-grip finish                             | -2     |
| <input type="checkbox"/> High-polish finish                             | -4     |
| <input type="checkbox"/> Safety grip with high-polished finish          | -7     |
| <input type="checkbox"/> Antimicrobial finish: 18", 24", 36" & 42" only | -AM    |


**Guide Specification**

Grab bar shall be fabricated of satin finish stainless steel with concealed mounting flanges in sizes and configurations as indicated. Install with Bradley Mounting Kits as indicated.

**ADA Compliant**

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

Orders composed of products indicated as **Bradex®** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.



**Bradex® Models**

| Configuration Number | Shipping Data |          | Configuration Number | Shipping Data |          |
|----------------------|---------------|----------|----------------------|---------------|----------|
|                      | Cu. Ft.       | Wt. Lbs. |                      | Cu. Ft.       | Wt. Lbs. |
| 001-18"•             | 0.14          | 2        | 001-42"•             | 0.15          | 4        |
| 001-24"•             | 0.14          | 3        | 001-42"-10•          | 3.14          | 37.67    |
| 001-30"              | 0.15          | 3        | 001-48"              | 0.25          | 4        |
| 001-36"•             | 0.15          | 3        | 059**                | 2.85          | 7        |
| 001-36-10•           | 2.40          | 30.46    |                      |               |          |

NOTE: These units must ship via common carrier.  
 \*\* 059: 40" x 52" Standard Dimensions.  
 • Indicates available Safety Grip. **Bradex®**