

Hook-Up Wire

UL STYLE 1015



APPLICATIONS

For use in internal wiring of electrical equipment, control panels, appliances, and grounding for use on industrial plan floor. Use as permitted in NEC Article 310 and NFPPA #79. Suitable for boat wiring in accordance with 33 CFR 183.425-435.

PART NO.	AWG	STRANDING	NOMINAL INSULATION THICKNESS (IN)	NOMINAL OD (IN)	NORMAL WEIGHT (Lbs/MFT)
1015-24-7-X	24	7/32	.030	.086	4.7
1015-22-7-X	22	7/30	.030	.091	5.5
1015-20-10-X	20	10/30	.030	.099	7.2
1015-18-16-X	18	16/30	.030	.106	9.3
1015-16-26-X	16	26/30	.030	.117	13
1015-14-41-X	14	41/30	.030	.132	19
1015-12-65-X	12	65/30	.030	.155	27
1015-10-105-X	10	105/30	.030	.175	39

CONSTRUCTION

Conductor	Class K stranded tinned copper
Insulation	Polyvinyl Chloride (PVC)
Temperature	90C
Voltage	600V
Colors	Standard Colors

COLOR CODE CHART

Cond & Color

X= Color

0 Black	5 Green
1 Brown	6 Blue
2 Red	7 Violet
3 Orange	8 Gray
4 Yellow	9 White

SPECIFICATIONS

- UL Standard 758 Application Wire
 - AWM 1015 105C 600V
 - AWM 1230 105C 600V
 - AWM 1032 90C 1000V
- MTW 90C 600V VW-1
- THW 75C WET/DRY 600V
- CSA TEW 105C 600V
- UL STANDARD 1426 BOAT CABLE
 - BC-5W2-16 AWG-10AWG

AVAILABLE PUT-UPS

100' Reels
500' Reels
1,000' Reels

Other lengths available. Please consult your representative for availability.

COMPLIANCE

- REACH
- RoHS



The information contained on this specification is intended to be used as a guide in product selection.