

Hook-Up Wire

UL STYLE 1061



APPLICATIONS

For use in internal wiring of electrical bookkeeping, accounting, time recording machines, or electrical equipment if within a chassis or protected from mechanical injury.

PART NO.	AWG	STRANDING	NOMINAL INSULATION THICKNESS (IN)	NOMINAL OD (IN)	NORMAL WEIGHT (Lbs/MFT)
1061-28-7-X	28	7/36	.010	.035	1.08
1061-26-7-X	26	7/34	.010	.039	1.46
1061-24-7-X	24	7/32	.010	.044	2.18
1061-22-7-X	22	7/30	.010	.051	3.29
1061-20-10-X	20	10/30	.010	.058	4.05
1061-18-16-X	18	16/30	.010	.068	6.12
1061-16-26-X	16	26/30	.010	.080	9.42

CONSTRUCTION

Conductor	Class K stranded tinned copper
Insulation	Semi-rigid Polyvinyl Chloride (SR-PVC)
Temperature	80C
Voltage	300V
Colors	Standard Colors available

COLOR CODE CHART

Cond & Color

X= Color

0 Black	5 Green
1 Brown	6 Blue
2 Red	7 Violet
3 Orange	8 Gray
4 Yellow	9 White

SPECIFICATIONS

- UL Standard 758 Application Wire
 - AWM 1061 80C 300V
- 22-28 AWG: M16878/1 TYPE B
 - 105C 600V

AVAILABLE PUT-UPS

100' Reels
500' Reels
1,000' Reels

Other lengths available. Please consult your representative for availability.

COMPLIANCE

- REACH
- RoHS



The information contained on this specification is intended to be used as a guide in product selection.