

Security Alarm Cable

SHIELDED PLENUM-RATED



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

PART NO.	AWG / COND	STRAND	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
				INCH	mm	INCH	mm	
22 AWG								
CL3P22/2-7S	22/2	7	59	.015	.38	.120	3.05	13
CL3P22/3-7S	22/3	7	59	.015	.38	.127	3.23	17
CL3P22/4-7S	22/4	7	59	.015	.38	.138	3.51	20
CL3P22/6-7S	22/6	7	59	.015	.38	.163	4.14	26
CL3P22/8-7S	22/8	7	59	.015	.38	.173	4.39	32
20 AWG								
CL3P20/2-7S	20/2	7	62	.015	.38	.139	3.53	19
18 AWG								
CL3P18/2-7S	18/2	7	65	.015	.38	.162	4.11	23
CL3P18/3-7S	18/3	7	65	.015	.38	.175	4.45	30
CL3P18/4-7S	18/4	7	65	.015	.38	.191	4.85	37
CL3P18/6-7S	18/6	7	65	.015	.38	.229	5.82	51
CL3P18/8-7S	18/8	7	65	.015	.38	.241	6.12	66
16 AWG								
CL3P16/2-7S	16/2	19	73	.015	.38	.187	4.75	30
CL3P16/4-7S	16/4	19	73	.015	.38	.218	5.54	49
14 AWG								
CL3P14/4-7S	14/4	19	75	.015	.38	.264	6.71	78

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted, aluminum mylar shielding with drain wire and an overall low smoke white PVC jacket with rip cord.

SPECIFICATIONS

Conductor	Bare Copper
Insulation	Low Smoke PVC
22 AWG	.007" PVC
20 AWG	.008" PVC
18 AWG	.009" PVC
16 AWG	.010" PVC
14-12 AWG	.012" PVC
Shield	Aluminum Mylar
Jacket	Low Smoke PVC

NEC Articles

- 22-16 AWG: FPLP/760, CMP/800, CL3P/725
- 14-12 AWG: FPLP, CL3P

Voltage Rating 300 V

Temp. Rating -25°C to 75°C

Drain Wire

- 24 AWG Tinned Copper

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

AVAILABLE PUT-UPS

- 1,000' Reels and Boxes
- 500' Reels and Boxes

Other lengths available. Please consult your representative for availability.

CABLE IDENTIFICATION

XX AWG XC (ETL)us TYPE CL3P/FPLP
c(ETL)us TYPE CMP 3054355

*14-12 AWG are not recognized by c(UL) or c(ETL).

COLOR CODE CHART

Cond & Color

1 Black	7 Orange
2 Red	8 Yellow
3 White	9 Purple
4 Green	10 Gray
5 Brown	11 Pink
6 Blue	12 Tan



The information contained on this specification is intended to be used a guide in product selection.