

Security Alarm Cable

UNSHIELDED

CMP/FT6 Rated, FPLP, CL2P, CL3P



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

PART NO.	AWG / COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
			INCH	mm	INCH	mm	

22 AWG

CL3P22/2-7N	22/2	7	.018	.457	.124	3.15	10
CL3P22/3-7N	22/3	7	.018	.457	.131	3.33	13
CL3P22/4-7N	22/4	7	.018	.457	.143	3.63	17
CL3P22/6-7N	22/6	7	.018	.457	.171	4.34	24
CL3P22/10-7N	22/10	7	.018	.457	.193	4.90	40
CL3P22/12-7N	22/12	7	.018	.457	.225	5.72	49

18 AWG

CL3P18/2-7N	18/2	7	.018	.457	.157	3.99	18
CL3P18/3-7N	18/3	7	.018	.457	.168	4.27	25
CL3P18/4-7N	18/4	7	.018	.457	.186	4.72	36
CL3P18/6-7N	18/6	7	.018	.457	.222	5.64	51
CL3P18/8-7N	18/8	7	.018	.457	.262	6.65	68
CL3P18/12-7N	18/12	7	.018	.457	.296	7.52	84

16 AWG

CL3P16/2-7N	16/2	19	.018	.457	.180	4.57	26
CL3P16/3-7N	16/3	19	.018	.457	.191	4.85	38
CL3P16/4-7N	16/4	19	.018	.457	.211	5.36	52

14 AWG

CL3P14/2-7N	14/2	19	.018	.457	.222	5.64	40
CL3P14/4-7N	14/4	19	.018	.457	.261	6.63	73

12 AWG

CL3P12/2-7N	12/2	19	.018	.457	.272	6.91	58
-------------	------	----	------	------	------	------	----

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted with an overall low smoke white PVC jacket with rip cord.

SPECIFICATIONS

Conductor	Bare Copper
Insulation	Low Smoke PVC
22 AWG	.007" PVC
20 AWG	.008" PVC
18 AWG	.009" PVC
16 AWG	.010" PVC
14-12 AWG	.012" PVC

Jacket Low Smoke PVC

NEC Articles

- 22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P

Voltage Rating 300 V

Temp. Rating 75°C

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

AVAILABLE PUT-UPS

1,000' Reels and Boxes
500' Reels and Boxes

Other lengths available. Please consult your representative for availability.

CABLE IDENTIFICATION

XX AWG XC (ETL)us TYPE CL3P/FPLP
c(ETL)us TYPE CMP 3054355

*14-12 AWG are not recognized by c(UL) or c(ETL).

COLOR CODE CHART

Cond & Color

1 Black	7 Orange
2 Red	8 Yellow
3 White	9 Purple
4 Green	10 Gray
5 Brown	11 Pink
6 Blue	12 Tan



The information contained on this specification is intended to be used a guide in product selection.

