

# STERLING

## WIRE & CABLE

### SWC-3070

22 AWG 4 pair 7 strand bare copper wire; .007" low-smoke PVC insulation; aluminum mylar shield with a 24 AWG 7 strand tinned copper drain wire; overall .017" natural low-smoke PVC jacket

CONDUCTOR	
AWG & Stranding	22 AWG, 7 Strand Bare Copper
Number of Conductors	8; 4 Pair
INSULATION	
Material	Low-smoke PVC
Wall Thickness	0.007"
Color Code	Red/Black, White/Brown, Green/Orange, Yellow
ASSEMBLY	
Lay Length	2.00" Pairs/3.00" Overall; 4 twists/ft.
Binder	N/A
Shield	Aluminum Mylar
Drain	24 AWG, 7 Strand Tinned Copper
JACKET	
Material	Low-smoke PVC
Wall Thickness	0.170"
Nominal Diameter	0.216"
Color	Natural
Weight	35 lbs/mft
MARKINGS	
Type	CL3P / CMP
Legend	Standard per UL + ACCESS CONTROL 22/84P-SH
Standard	Sequential footage marked 1-1000
ELECTRICAL CHARACTERISTICS	
UL Type	CL3P / CMP
Temperature Rating	75C
Capacitance	47 pF/ft

\*\* All measurements are nominal.