



LE1015

FEATURES

- + True flat, bezel free design
- + Durable and sturdy base
- + Supports integrated MSR and 2nd display
- + Proven reliable performance
- + Built-in universal power supply
- + Built-in speakers
- + USB touch interface

15in LCD Touch Screen Monitor

The Logic Controls LE1015 true flat, bezel free touch monitor is designed and manufactured to meet the requirements of retail or restaurant operations as part of a Point of Sale system. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The LE1015 touch monitor also facilitates quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



LE1015 specifications

LCD TOUCH PANEL

LCD size:	15in (38.1cm)
Display active area:	11.9in x 8.9in (30.4cm x 22.8cm)
Brightness:	250 cd/m ²
Response time:	12ms
Contrast ratio:	800:1
Resolution:	XGA 1024 x 768 @ 75Hz, 16.2M colors
Viewing angle:	(CR≥10) Horizontal: 160°, Vertical: 145°
Touch screen:	5-wire resistive touch panel, USB interface

MECHANICAL

Net weight:	12 lbs (5.5 kg)
Dimension (W x D x H):	14.3in x 9.0in x 12.8in (36.4cm x 23.0cm x 32.6cm)
Color:	Black

ELECTRICAL

Power supply:	Built-in universal power
Input:	100~240VAC, 50/60Hz
Power consumption:	30W max
Power saving mode:	1W max
Power off mode:	0.5W max

ENVIRONMENTAL

Operating temperature:	41°F to 104°F (5°C to 40°C)
Relative humidity:	20% – 80%, non-condensing

MISCELLANEOUS

Plug & Play:	DDC2B
VESA wall mount compatible:	3.94in x 3.94in (10.0cm x 10.0cm)
Power management:	VESA DPMS
Magnetic stripe reader (optional):	Track 1/2/3, USB interface
Customer display (optional):	8in LCD or 2×20 VFD, USB interface

