



UPC Code: 078477692325

Country Of Origin: China

# DSL06-1LZ

Decora Slide Dimmer Switch for Dimmable LED, Halogen and Incandescent Bulbs

Decora Slide Dimmer. 600W-120VAC incandescent, and 300W-120VAC dimmable LED and CFL, 60Hz., single pole or 3-way control when used with 3-way switch, wallplate sold separately. Can be used to comply with 2016 California Title 24, Part 6, Indoor Lighting Switching Devices and Controls - White, Ivory & Almond

- INNOVATIVE Designed to dim LED bulbs. For the best bulb pairings, refer to the "find a bulb" button below
- FLEXIBLE Can be used in a single-pole or 3-way installation (with a 3-way switch, sold separately). No neutral wire required for installation
- CONVENIENT Separate ON/OFF rocker switch allows you to set and keep preferred dimming level
- ADVANCED Adjustment switch to modify the minimum light level in order to maximize the dimming range if flickering occurs at lower dimming levels
- Now available in bulk pack white color only

#### **Technical Information**

### **Product Features**

**Action :** Rocker Switch for ON /OFF, slide bar for lighting level control

Available Colors: Ivry-I Wht-W Gry-G Blk-E Brwn-B Light Almond-T, R-Red

**Color :** White, Ivory, Light Almond

Frequency: 60 Hz

Light: Locator light that can be

turned off

Load Rating: 600W

Incandescent, 300W LED and

CFL

**Load Type :** Incandescent, Dimmable LED, Dimmable CFL

**Ordering Notes :** Included White, Ivory and Light Almond Color Kit

**Preset :** Slide bar preserves desired lighting level

Protection: Radio/TV Filter

**Standards and Certifications** 

: cCSAus, NOM

Style Name: Decora

Switch Type: Single-Pole & 3-

Way

Torque Range: 14 – 18 in.-lbs

Type: Dimmer

Voltage: 120 VAC

Wallplate : Order Separately
Warranty : 5-Year Limited

#### **Features and Benefits**

- New aesthetically pleasing design with rocker switch and slender dimmer control slide bar
- Integrated linear full-range slide control for easy, precise operation
- Controls a variety of dimmable LED and CFL lamps
- Compatible with Incandescent and Halogen lamps
- Single pole or 3-way operation (when using 3-way switch);
   packaged with White, Ivory, and Light Almond color change kits
- Additional color change kits available in Black, Brown, Red and Gray
- Slim, compact housing fits easily into a standard wallbox and is suitable for multi-gang installations with other Decora products
- The slide bar location preserves the selected brightness level when the dimmer is switched OFF
- Microprocessor control offers flexibility to program LEDs and CFLs for best performance
- Switch under the color change kit to turn locator light ON /OFF
- No fins for multi-gang installation
- Screw terminals with back wire capability for easier installation, a Neutral wire is not required for operation
- Built-in radio/TV interference filter

## Patents\*

CA2798964 US8664886 US8944859 US9431192 US9681526

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## **SPECIFICATION SUBMITTAL**

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

# © 2024 Leviton Manufacturing Co., Inc.