



# 16262-HGR

15 Amp Decora Plus Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Decora Plus Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage :** 1/2 HP

### Electrical Specifications

**Amperage :** 15 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :** Withstands 2000V per UL498

**Grounding :** Self-Grounding

**Pole :** 2

**Temperature Rise :** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage :** 125 VAC

**Wire :** 3

### Environmental Specifications

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40° C to 60°C

### Material Specifications

**Body Material :** Nylon

**Clamp Nuts :** Zinc-Plated Steel

**Color :** Red

**Face Material :** Nylon

**Ground Clips :** Brass-Plated

**Grounding Screw :** Brass 8-32

**Line Contacts :** Brass Triple-Wipe 0.040" Thick

**Strap Material :** Steel

**Terminal Screws :** Brass 10-32

**Yoke :** Zinc-Plated Steel

### Mechanical Specifications

**Product ID :** Ratings are permanently marked on device

**Screw Terminal Torque :** 14-18 in-lbs

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

### Product Features

**Brand :** Decora Plus

**Color :** Red

**Device Type :** Duplex Receptacle Outlet

**Feature 4 :** Smooth Face

**Grade :** Extra Heavy-Duty Hospital Grade

**Color :**  Red

**UPC Code :** 078477818749

**Country Of Origin :** Please Contact Customer Service

**NEMA :**  5-15R

### Available Colors :



Gray



Ivory



White

**Termination** : Back or Side Wire

**NEMA** : 5-15R

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File 152105


**NEMA** : WD-6

**NOM** : 057

**UL498HG** : File E13399

**Warranty** : 10-Year Limited

## Wiring Diagram



### SPECIFICATION SUBMITTAL

<p>JOB NAME:</p> <input type="text"/>	<p>CATALOG NUMBERS:</p> <input type="text"/>
<p>JOB NUMBER:</p> <input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.