

PRODUCT-DETAILS

## **N2810 AN**

## Switch intermediate Rocker/button Intermediate switch with LED exchangeable Anthracite - Zenit



| Canara | I Infor | mation |
|--------|---------|--------|

| Extended Product Type | N2810 AN  |
|-----------------------|---|
| Product ID            | 2CLA281000N1801   |
| EAN                   | 8427238085920   |
| Catalog Description   | Switch intermediate Rocker/button Intermediate switch with LED exchangeable<br>Anthracite - Zenit |
|                       | Color: Anthracite.  |
|                       | Rated voltage: 110 - 250 Vac  |
|                       | Rated current: 16 AX.   |
| Long Description      | Rated power iLED (230/127 Vac): 200/100 W.<br>Screwless terminals                                 |

Installation

Instructions and 2CLX210109N1001 Manuals

**Technical** 

Data Sheet, Technical 9AKK10103A5108
Information

Optional: locator LED lamp N2192.

Size: 1,5 modules.

N2810 AN 2

| nction   | Function lighting: Orientation                      |
|--|---|
| ted Voltage (U <sub>r</sub> )  | 250 \   |
| ted Current (I <sub>n</sub> )  | 16 /  |
| iximum Switching<br>rrent  | Fluorescent Lamps 16                                |
| mber of Rocker<br>ritches  |   |
| sign Range   | Zeni  |
| ring Configuration   | Intermediate switch                                 |
| tuator Type  | Rocker/butto  |
| nnection Type  | Plug Clamp  |
| тр Туре  | LED exchangeable                                    |
| ounting Type   | Flush Mounted                                       |
| pe of Fastening  | Engage (Snap  |
| rface Finishing  | Deco<br>Mat   |
| iterial  | Plasti  |
|  | Thermoplasti  |
| bel Space Provided   | No  |
| mination .   | Optiona   |
| lor<br>mber of Batteries   | Anthracite  |
| nvironmental   |   |
| nbient Air   | 0 5 .250  |
| mperature  | Operation -5 +35 °C<br>Storage -5 +50 °C            |
|  |   |
| mperature  | Storage -5 +50 °C                                   |
| mperature gree of Protection nflict Minerals porting Template MRT)   | Storage -5 +50 °C                                   |
| mperature gree of Protection  nflict Minerals porting Template MRT)  imensions                                   | Storage -5 +50 °C<br>IP20<br>9AKK108468A3363        |
| mperature gree of Protection  nflict Minerals porting Template MRT)  imensions  oduct Net Width                  | Storage -5 +50 °C IP20 9AKK108468A3363              |
| mperature gree of Protection  nflict Minerals porting Template MRT)  imensions  oduct Net Width oduct Net Height | Storage -5 +50 °C IP2C 9AKK108468A3363  33 mn 44 mn |
| mperature gree of Protection  nflict Minerals porting Template MRT)  imensions  oduct Net Width                  | Storage -5 +50 °C IP20 9AKK108468A3363              |
| mperature gree of Protection  nflict Minerals porting Template MRT)  imensions  oduct Net Width oduct Net Height | Storage -5 +50 °C IP2C 9AKK108468A3363  33 mn 44 mn |

| Certificates | and Dec | larations |
|--------------|---------|-----------|
|--------------|---------|-----------|

Declaration of 9AKK106930A5900
Conformity - CE

| Cla | ssific | ation | c |
|-----|--------|-------|---|

| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
|---------------|--|
| ETIM 9        | EC001590 - Installation switch                             |
| ETIM 8        | EC001590 - Installation switch                             |

N2810 AN 3

 WEEE B2C / B2B
 Business To Consumer

 CN8
 85365080

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Mechanical\ Controls$ 

