

T5632-E

3.6A USB Type-A/Type-A Wall Outlet Charger with 15A Tamper-Resistant Receptacles

Combination Duplex Receptacle/Outlet and USB Charger. 15 Amp, 125 Volt, Decora Tamper-Resistant Receptacle/Outlet, NEMA 5-15R. 3.6 Amps, 5VDC, 2.0 Type A USB Chargers. Grounding, Side Wired & Back Wired - Black

- SMART - Built-in smart chip recognizes the individual device's charging requirement to optimize the charge
- POWERFUL - Two high-powered charging ports with 3.6A of charging power
- CONVENIENT - No more searching for charging adapters! Upgrade your existing outlets so you can charge up to two USB powered electronics at once, leaving the outlets free for additional power needs
- EASY - Compact design fits in a standard wallbox and works with Decora and Decora Plus screwless wallplates.




Color :  Black

UPC Code : 078477683927

Country Of Origin : China

NEMA :  5-15R

Available Colors :



Technical Information

Electrical Specifications

Amperage : 15 A
Flammability : Rated V-0 per UL 94
Grounding : Grounding
Horsepower Rating : 15A-1/2 HP
Operating Temperature : -10° C to 40°C
Ratings : 15A-125V

Environmental Specifications

Body Material : Thermoplastic
Color : Black
Cover Material : Thermoplastic
Flammability : Rated V-0 per UL 94
Operating Temperature : -10° C to 40°C
Strap Material : Steel

Material Specifications

Amperage : 15 A
Body Material : Thermoplastic
Color : Black
Cover Material : Thermoplastic
Product ID : Stamped on Strap
Strap Material : Steel
Terminal Accom. : 14-12 AWG
Termination : Back & Side
Torque Range : 14 – 18 in.-lbs

Mechanical Specifications

Amperage : 15 A
Color : Black
Grade : Residential /Commercial Specification Grade
Product ID : Stamped on Strap
Terminal Accom. : 14-12 AWG
Termination : Back & Side
Torque Range : 14 – 18 in.-lbs

Product Features

Amperage : 15 A
Brand : Decora

Standards and Certifications

FCC Part 15 : Class B
Listed : cCSAus
NOM : 057

Grade : Residential
/Commercial Specification
Grade

UL 1310 : Yes

UL 498 : Yes

Grounding : Grounding

Warranty : 2-Year Limited

Horsepower Rating : 15A-1/2
HP

NEMA : 5-15R

Product Type : Outlet/USB
Combo

Ratings : 15A-125V

Type : Type A/A Duplex
Receptacle

Voltage : 125 VAC

Wallplate : Not Included

Features and Benefits

- Perfect for use in residential applications such as kitchens, bedrooms and home offices and in commercial applications such as hotels, airports, restaurants and cafes, salons, office cubicles and college dorm rooms
- Smart chip recognizes and optimizes the charging requirements of individual devices
- Tested to withstand over 10,000 insertions.
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- Fits in a standard wallbox, is compatible with standard wallplates and can be multi-ganged with other devices
- Easy to install. Can replace existing outlets
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates. Wallplate sold separately

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	<input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.