

DS-PDTT15AM-LM-WB Wireless Triple Signal Detector

PDTT15AM is a unique two-way wireless outdoor triple signal detector with Anti-masking feature, designed to protect the outdoor areas of your property in most harsh environment and alarm before an intruder breaks in your house

- · 90°@180° adjustable coverage
- · IP65 weather resistance for outdoor application
- · Active IR anti-masking
- Multiple enrollment methods and easy installation
- Frequency hopping against jamming for reliable transmission



Specification

| Detection Performance | |
|-----------------------------------|---|
| Detection Method | Passive Infrared, Microwave |
| Detection Range | 15m |
| Detection Angle | 90° @ 180° adjustable |
| Detection Zones | 92 |
| Detectable Speed | 0.3 ~ 2m/s |
| Sensitivity | Auto,Low |
| White Light Filter | 10000lux |
| Microwave Frequency | 24GHz(24.15 ~ 24.25GHz) |
| Pet Immunity | 40Kg |
| Digital Temperature Compensation | Support |
| Anti-masking | Support |
| Adaptable Coverage | Support |
| | Pattern mask included |
| Feature | |
| Digital Processing | Tri-Signal Logic |
| Sealed Optics | Support |
| Tamper Protection | Front,Rear |
| Environment Temperature Indicator | Support |
| Signal Strength Indicator | Support |
| Anti-Sway Analytics | Support |
| Interface | |
| Power Switch | Power Up Enrolling |
| LED Indicator | Green(Top PIR), Red(Microwave), Orange(Bottom PIR), Green+Orange(Mask), Blue(Alarm) |
| Transmission | |
| Transmission Technology | Tri-X Wireless |
| Transmission Method | Two-Way RF Wireless |
| Transmission Frequency | 433MHz |
| Transmission Security | AES-128 Encryption |
| Transmission Range(Free Space) | 1Km |
| Frequency Hopping | Support |
| Enrolling Method | Power up,Remote ID,QR Code |
| Electrical Characteristics | |
| Standard Battery Life | Up to 5 years (standby time) |
| Power Supply | Battery Powered |
| Battery Type | CR123A × 5 |
| Typical Voltage | 3V |
| General | |
| Operation Temperature | -25 °C to 60 °C (-13 °F to 140 °F) |



| Storage Temperature | -25 °C to 60 °C (-13 °F to 140 °F) |
|----------------------|------------------------------------|
| Operation Humidity | 10% to 90% |
| IP Rate | IP65 |
| Dimension(WxHxD) | 75mm × 202mm × 73mm |
| Weight | 600g |
| Mounting Height | 0.8 to 1.2m |
| Mounting Method | Wall |
| Application Scenario | Outdoor |

Available Model

DS-PDTT15AM-LM-WB

Accessory

Included



Optional







Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ





