

DS-PS1-I-WB Wireless Internal Sounder

The wireless internal sounder, supporting 433 MHz wireless communication, Tri-X wireless protocol, multiple enrollment methods, two-way wireless communication, multiple alarm sounds, and strobe light indication, is used for instant alarm alerting.

HIKVISION

Key Features

- 433 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 90 to 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

Available Model

• DS-PS1-I-WB (433MHz)







| Model | | DS-PS1-I-WB |
|-------------------------|-----------------------|---------------------------------------|
| RF | Frequency | 433 MHz |
| | Modulation | 2GFSK |
| | Method | Two-way communication |
| | RF encryption | AES-128 |
| | RF distance | 900m (open area) |
| Electrical & battery | Power | Battery |
| | Consumption | Static consumption: 30 to 40uA |
| | Battery life span | 3 CR123A, 3 years in work status |
| | | (triggered every two weeks and |
| | | alerting 90 s for each triggering) |
| Interface and component | Power switch | Supported |
| | Tamper switch | Supported, Front and rear |
| | | tamper-proof |
| | Indicator | Indicator: Red/Green/Amber |
| | | Strobe light: Red/Blue |
| | Buzzer | Decibel: 90 to 110 dB |
| General | Operation temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| | Operation humidity | 10% to 90% (no condensing) |
| | Color | White |
| | Material | PC+ABS |
| | Dimension (W × H × D) | 88× 88 × 32 mm (3.46" ×3.46" × 1.26") |
| | Weight | 169.5 g (6.0 oz) |
| | Installation | Wall mounting |
| Approvals | FCC | Supported |
| | CE/CB | Supported |
| | RCM | Supported |
| | Rohs/Reach/WEEE | Supported |



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

sales.usa@hikvision.com **Hikvision Australia** T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com