

A red banner with rounded ends is located in the upper left quadrant. It contains the product name "DS-PDCL12DT-EG2" and "Wired Dual-Tech Ceiling Detector" in white, sans-serif text.

It is the ceiling dual-tech detector that uses our latest quad element sensor and 24GHz smart microwave technology, which brings higher picking-up performance and lower false alarm rate in the field

- Digital quad pyro sensor + 24GHz microwave
- Automatic sensitivity
- Wide voltage adaptation and on-board EoL resistor



ONLY THE BEST DEALS FOR SECURITY PRODUCTS

SECUREON.COM.AU

P 1300 888 767



www.hikvision.com

▪ Specification

| Detection Performance | |
|----------------------------------|---|
| Detection Method | Passive Infrared, Microwave |
| Detection Range | 12 m |
| Detection Angle | 360° |
| Detection Zones | 172 |
| Detectable Speed | 0.3 to 2m/s |
| Sensitivity | Auto, Low |
| White Light Filter | 6500lux |
| Microwave Frequency | 24 GHz(24.15 ~ 24.25 GHz) |
| Digital Temperature Compensation | Support |
| Creep Zone Protection | Support |
| Feature | |
| Digital Processing | Support |
| Sealed Optics | Support |
| Tamper Protection | Front |
| Interface | |
| LED Indicator | Green(PIR), Red(Microwave), Blue(Alarm) |
| Electrical characteristics | |
| Power consumption | 100 mA Max |
| Electrical Characteristics | |
| Power Supply | 9 to 16 VDC |
| Typical Voltage | 12 VDC |
| General | |
| Operation Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Storage Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Operation Humidity | 10% to 90% |
| Dimension(W × H × D) | φ120 mm × 33.2 mm |
| Weight | 138 g |
| Mounting Height | 2.4 to 4 m |
| Mounting Method | Ceiling |
| Application Scenario | Indoor |

▪ Available Model

DS-PDCL12DT-EG2

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com