



## Technical Sheet

### ADJUSTABLE PEDESTAL 8/20 MM FOR PAVING

<b>Material</b>	Filled Polypropylene
<b>Color</b>	Black and red
<b>Origine</b>	Made in France
<b>Guarantee</b>	10 years
<b>Purpose</b>	Tiled terrace, concrete tiles or duckboards
<b>Use</b>	Only pedestrian
<b>Height</b>	Adjustable from 8 to 20 mm (0 <sup>5</sup> / <sub>16</sub> in to 0 <sup>25</sup> / <sub>32</sub> in)
<b>Thickness of lugs</b>	3 mm
<b>Maximum charge</b>	Up to 1 Ton
<b>Resistance to temperature variations</b>	-40° C to +60° C
<b>Resistance to atmospheric agents</b>	Freezing, UV
<b>Resistance to acids and chemicals</b>	Yes (can be laid next to a swimming pool)

## Norms & conformity

### ADJUSTABLE PEDESTALS RINNO

**DTU 43.1 (NF P 84.204)** Waterproofing of flat roofs and inclined roofs with load-bearing masonry elements.

Extract « The traffic coating is executed in accordance with the provisions of article 7,213,232 supplemented by the following provisions with regard to the pedestals: the underside of the pedestals must be made of rigid material; the section of the face in contact with the asphalt must be greater than or equal to 300 cm<sup>2</sup>; the pressure under permanent load on the asphalt must be less than or equal to 20,000 Pa (0.2 daN / cm<sup>2</sup>) ».

Characteristics: the minimum section of each face is 100 cm<sup>2</sup>. The breaking strength of the pedestals must be such that they support 2.5 KN during an offset loading test on 1/4 of the pedestal and 5.0 KN during a loading test uniformly distributed over the section of the pedestal.

**DTU 51.4 P1-1 (CCT)** Building work External wooden pallets.

**DTU 20.12 (NF P 10.203)** Structural design of masonry for roofs intended to receive a waterproofing coating.

**NF P06.001** Calculation basis for constructions-building operating costs.

**DTU P06.002** Wind rules NV65.

**DTU P06.006** Rule N84, action of snow on buildings.

**NF EN 1339** Concrete tiles.