




Model: RHX-WM1

# Wall Mount Relative Humidity Transmitter



## FEATURES & BENEFITS

- Designed For Wall Mount Applications
- Accurate To +/- 3 % Relative Humidity
- Available with 0-1Vdc, 0-5Vdc or 4-20mA Output
- Includes Mounting Hardware & Mounting Plate

## APPLICATIONS

- Laboratory and Research Facilities
- Storage Room, Wine Cellar
- Workplace Environmental Monitoring

## DESCRIPTION

Model RHX-WM1 transmitter features fast response time, long-term stability, good accuracy and repeatable measurements. Designed for wall mounting, this model transmitter has an accuracy of +/- 3 % RH and provides an industry standard analog output of 0-5 Vdc, 0-1Vdc, or 4-20mA.

## Specifications

Humidity Range:	0 – 100 % RH
Humidity Accuracy:	+/- 3 % RH (15 to 85 %) @23°C
Ambient Temperature:	-13 to 185 °F (-25 to 85 °C)
Wiring Connection:	Internal terminal block (16-24 AWG)
Dimensions:	1.06 x 2.13 x 2.95" (27 x 54 x 75mm)



State-of-the-art Electronic Module

## Available Models

Model Number	Output	Operating Voltage	Description
RHX-WM1-01	0 – 1V DC	7 to 24V DC	Wall Mount Humidity Transmitter, Voltage Output
RHX-WM1-05	0 – 5V DC	7 to 24V DC	Wall Mount Humidity Transmitter, Voltage Output
RHX-WM1-420	4 – 20 mA	8 to 12V DC	Wall Mount Humidity Transmitter, Current Output

© 2014 :: Imagine Instruments LLC :: 4500 Williams Drive, Ste 212-318 :: Georgetown, TX 78633 :: p. (855)574-6243  
e-mail: info@imagineinstruments.com :: www.imagineinstruments.com

Note: Continued product improvements make specifications subject to change without notice.  
Check www.imagineinstruments.com for the latest product information and updates

Released: 21 March, 2014 :: Rev: A