AXIOM®-DV-APS

Height: 23.6" Width: 9.0" Depth: 22.5" (59.9cm) (22.9cm) (57.2cm)





- Adjusts automatically to varying water pressure
- Electronic diagnostics and built-in tank drain make service easier
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels
- Large 200oz. (5.9L) tank provides back-to-back brewing capacity
- Ensure coffee quality with programming for brew level, cold brew lock- out and tank temperature, set easily from the front of the machine
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature precision
- Brews directly into 1.9 to 3L airpots
- Energy-saver mode reduces tank temperature during idle periods
- Hot water faucet
- SplashGard® funnel deflects hot liquids away from the hand
- Dual voltage adaptable (Can operate at 120V/15 amp or 120/208-240V/20 amp)
- PROP 65 Warning Decal included in packaging with equipment
- · Servers not included unless otherwise noted

Agency:





Specifications

Product #: 38700.0010 Faucet: Upper

Water Access: Plumbed

Finish: Stainless
Funnel: Black Plastic

Additional Features

DBC

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz
120	12.5	1500	Yes	NEMA 5-15P	67	60°F (15.5°C)	1	2	60
120/208	13	2680	-	N/A	121	60°F (15.5°C)	-	-	-
120/240	15	3550	-	N/A	121	60°F (15.5°C)	-	-	-

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements

PSI kPa		Fitting Supplied	Water Flow Required (GPM)			
20-90	138-621	1/4" Male Flare Fitting	-			


CAD Drawings


2D	Revit	KLC
•		

MARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.





Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	23.6 in.	9.0 in.	22.5 in.	29.0 in.	11.9 in.	25.8 in.	35.200 lbs	5.145 ft³
Metric	59.9 cm	22.9 cm	57.2 cm	73.7 cm	30.2 cm	65.6 cm	15.967 kgs	0.146 m³



Related Products & Accessories: AXIOM®-DV-APS(38700.0010)



FILTERS,REGULAR1M 500/2 50/CL

Product #: 20115.0000





Serving & Holding Options: AXIOM®-DV-APS(38700.0010)



SINGLE PK

Product #:13041.0001



AIRPOT, 2.5L GL PB 6/ CASE

Product #:13041.0101



AIRPOT, 2.2L GL PB SINGLE PK

Product #:28696.0002



AIRPOT, 2.2L GL PB 6/ CASE

Product #:28696.0006



AIRPOT, 2.5L SST LA SINGLE PK

Product #:32125.0000



AIRPOT, 2.5L SST LA 6/ CASE

Product #:32125.0100



AIRPOT, 3.0L SST LA SINGLE PK

Product #:32130.0000



AIRPOT, 3.0L SST LA 6/ CASE

Product #:32130.0100



AIRPOT, 2.2L GL LA 6/ CASE

Product #:32700.0000



AIRPOT, 3.8L SST LA SINGLE PK

Product #:36725.0000



CASE

Product #:36725.0100



SINGLE PK

Product #:44311.0000

