### AXIOM®-DV-3 (2U/1LWarmer)

Height: 18.9" Width: 8.4" Depth: 22.1" (48.0cm) (21.3cm) (56.1cm)





- Adjusts automatically to varying water pressure
- Automatic warmer shut-off
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels
- · Electronic diagnostics and built-in tank drain make service easier
- Ensure coffee quality with programming for brew level, cold brew lock- out and tank temperature, set easily from the front of the machine
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control
- · Large 200oz. (5.9L) tank provides back-to-back brewing capacity
- Energy-saver mode reduces tank temperature during idle periods
- Hot water faucet
- SplashGard® funnel deflects hot liquids away from the hand
- Dual voltage adaptable (Can operate at 120V/15 amp or 120/208-240V/20 amp)
- · Servers not included unless otherwise noted

Agency:

#### **Specifications**

Water Access: Plumbed Warmers: Two Upper/ One Lower

Finish: Stainless
Funnel: Black Plastic

**Electrical & Capacity** 

Volts*	Amps	Watts	Cord Attached	Plug Type	Plug Type 8oz cups/hr 236ml cups/hr		Phase	# Wires plus Ground	Hertz	
-	-	-	-	-	61	60°F (15.5°C)	-	-	-	

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

#### Plumbing Requirements


	<u> </u>			
PSI	kPa	Fitting Supplied	Water Flow Required (GPM)	
20-90	138-621	1/4" Male Flare Fitting	-	

#### **CAD Drawings**

Additional Features

2D	Revit	KLC
•		





	Unit				Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume		
English	18.9 in.	8.4 in.	22.1 in.	23.8 in.	12.5 in.	26.5 in.	-	4.566 ft <sup>3</sup>		
Metric	48.0 cm	21.3 cm	56.1 cm	60.3 cm	31.8 cm	67.4 cm	-	0.129 m³		



# Related Products & Accessories: AXIOM®-DV-3 (2U/1LWarmer)(38700.6008)



STOVE,WX2 120V/200W

Product #: 06310.6000



STOVE,WX1 120V/100W

Product #: 06450.6000





## Serving & Holding Options: AXIOM®-DV-3 (2U/1LWarmer)(38700.6008)



EASY POUR®,(BLK) 1/CS

Product #:06100.0101



EASY POUR®,(BLK) 2/CS

Product #:06100.0102



EASY POUR®, (BLK) 3/CS

Product #:06100.0103



EASY POUR®,(BLK) 6/CS

Product #:06100.0106



EASY POUR®,(BLK) 12/

Product #:06100.0112



EASY POUR®,(BLK) 24/

Product #:06100.0124



EASY POUR®,(ORN) 1/ CS

Product #:06101.0101



EASY POUR®,(ORN) 2/

Product #:06101.0102



EASY POUR®,(ORN) 3/

Product #:06101.0103



EASY POUR®,(ORN) 24/ CS

Product #:06101.0124



DECANTER,GLASS-BLK 12C 24/CS

Product #:42400.0024



DECANTER,GLASS-BLK 12CUP 1PK

Product #:42400.0101



DECANTER,GLASS-BLK 12C 3/CS

Product #:42400.0103



DECANTER,GLASS-ORN 12C 24/CS

Product #:42401.0024



DECANTER, GLASS-ORN 12 CUP 1PK

Product #:42401.0101



12C 3/CS

Product #:42401.0103