H5X® Element SST

Height: 28.5" Width: 7.6" Depth: 18.9" (72.4cm) (19.3cm) (48.0cm)



- LED display provides simple temperature adjustment
- Thinsulate® tank insulation provides increased energy efficiency
- Digital thermostat provides constant and accurate temperatures of 60°- 212°F (15.6°-100°C)
- Programmable "Energy Saver Mode" reduces operating cost during idle periods
- The perfect tool for added control over quality coffee and tea
- Contemporary, space-saving design

Agency:

Specifications

Product #: 43600.6002 **Temp. Setting:** 212°F (100.000°C)

Water Access: Plumbed

Finish: Stainless
Faucet: Upper

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz	
-	-	-	-	-	-	60°F (15.5°C)	-	-	-	

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements

PSI kPa		Fitting Supplied	Water Flow Required (GPM)				
20-90	138-621	1/4" Male Flare Fitting	-				

CAD Drawings

Additional Features

2D	Revit	KLC
•		



Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	28.5 in.	7.6 in.	18.9 in.	32.3 in.	10.8 in.	20.4 in.	-	4.120 ft ³
Metric	72.4 cm	19.3 cm	48.0 cm	82.1 cm	27.5 cm	51.8 cm	-	0.117 m³



Related Products & Accessories: H5X® Element SST(43600.6002)







Serving & Holding Options: H5X® Element SST(43600.6002)

Serving and Holding selections are currently unavailable. Please contact your sales representative to find out more information.

