



Cleanware

SERIAL NO.:

XXXXXXXXXX

MODEL: Cleanware HT-E

60Hz 1 PH 2 WIRE



Intertek

5013646

Conforms to NSF STD 3

| | <u>208 VOLT</u> | | <u>230 VOLT</u> | |
|--------------|-----------------|---------------|-----------------|---------------|
| WASH MOTOR | 3/4 HP | 3.8 A | 3/4 HP | 3.8 A |
| DRAIN MOTOR | 1 HP | 0.3 A | 1 HP | 0.3 A |
| RINSE MOTOR | 0.25 kW | 1.8 A | 0.25 kW | 1.8 A |
| WASH HEATER | 3.2 kW | 15.2 A | 3.9 kW | 16.8 A |
| RINSE HEATER | 4.5 kW | <u>21.7 A</u> | 5.5 kW | <u>24.0 A</u> |
| TOTAL LOAD | | 25.8 A* | | 27.8 A* |

*NOTE: HEATERS AND MOTORS DO NOT OPERATE AT THE SAME TIME.
ELECTRICAL LOADS BASED ON HIGHEST AMP DRAW.



Intertek

5013646

Conforms to UL STD 921

Certified to CSA
STD C22.2 No.168

OPERATING PARAMETERS

| | |
|--------------------------|------------|
| MINIMUM WASH TEMP | 150 °F |
| MINIMUM RINSE TEMP | 180 °F |
| MIN. INCOMING WATER TEMP | 110 °F |
| WASH CYCLE TIME | 92 SEC |
| RINSE CYCLE TIME | 9 SEC |
| WATER FLOW PRESSURE | 20 ± 5 PSI |

CAUTION: IF THIS MACHINE IS CONNECTED TO A CIRCUIT PROTECTED BY FUSES, USE ONLY 35 A TIME-DELAY FUSES MARKED D OR OVERCURRENT PROTECTION.

ATTENTION: SE CONNECTER A UN MINIMUM D'ALIMENTATION 35 A
DELAI FUSIBLE DE TYPE TEMPS OU LA PROTECTION CONTRE LES SURINTENSITES.

MINIMUM CIRCUIT AMPACITY

@208 VOLTS: 31.8 AMPS

@230 VOLTS: 34.7 AMPS

MAXIMUM OVERCURRENT PROTECTION

@208 VOLTS: 35 AMPS

@230 VOLTS: 35 AMPS

Made in Italy
Jackson WWS, Inc.
Via Maggior Piovesana 154
31015 Conegliano (TV)
0438.23377
09905-004-66-74-B