

DINING ROOM SERVICE CART

- STAINLESS STEEL
- DRY OR MOIST HEAT OPERATION

- MOBILE
- PLUG-IN OPERATION

Model Series: HRSC-M-2

APPLICATION:


-Retirement & Nursing home meal service

SPECIFICATIONS:

- -Stainless steel; Type 304
- -"Heliarc" and spot-welded construction
- -Solid full base with full length reinforcing channels
- -Equipped with 2 full size food wells above 900 Watts Per well; 1800 Watts Total
- -1220 pan size standard with optional adapters for modular fractional sized pans
- -Each well and each electrical option runs on an individual circuit breaker
- -Each well is individually controlled by a variable heat setting thermostat with heat cycling "on/off" pilot light indicator
- -Well controls are mounted on control panel located at front right side
- -All wells have individual drains connected to a
- common manifold and spigot in enclosed rear compartment of unit
- -Drain spigot comes with heat resistant flexible drain hose with hose holder/clamp
- -Lower base area is open on operator side with enclosed back and sides
- -With a recessed plate shelf beside control panel
- -With intermediate adjustable shelf in base
- -Ergonomic push handle with rubber grips at front of unit
- -Wrap-around perimeter bumper on base with internal stainless steel core for strength and durability
- -Approved power supply cord with 3 prong end cap and cord hanger at back of unit in enclosed compartment
- -2 5" Heavy duty swivel plate casters
- 2-5" Heavy duty swivel plate casters with top lock brakes
- -CSA approved

OPTIONAL FEATURES: [1]

- -HB > Base heater
- -HD > Hinged doors on base
- -HWD > Heated warming drawer(s)
- -CES > Cantilever 1.6mm s/s top extension shelf at back of unit with cut-outs to accommodate 2 > 1/3 size pans
- -DWS > Drop work shelf (remove basic shelf)
- -OS4 > Overshelf (4 pan capacity pans not included)
- -PA > Pan adaptors
- -SSC or SSG > Solid surface décor top (Corian, granite, etc.)
- -LAM > Laminate décor panels on sides













DINING ROOM SERVICE CART

- STAINLESS STEEL
- DRY OR MOIST HEAT OPERATION


- MOBILE
- PLUG-IN OPERATION

Model Series: HRSC-M-2

ELECTRICAL DATA:

120 Volt, 60Hz, 1Ph, 1800 Watts 208 Volt, 60Hz, 1Ph, 1800 Watts

120/208 Volt; 60Hz, 1Ph, 1800 Watts





| MODEL | OPTIONAL FEATURE | OVERALL WIDTH | OVERALL DEPTH | OVERALL HEIGHT |
|------------------|---|------------------|------------------|-----------------|
| HRSC-M-2 | BASIC - NO FEATURES | 32" - 813mm | 37" - 940mm | 36.25" - 920mm |
| HRSC-M-2-CES | CANTILEVERED PAN SHELF | 32" - 813mm | 44" - 1117mm | 36.25" - 920mm |
| HRSC-M-2-HB | HEATED BASE | 32" - 813mm | 37" - 940mm | 36.25" - 920mm |
| HRSC-M-2-HB-CES | HEATED BASE & CANTILEVERED SHELF | 32" - 813mm | 44" - 1117mm | 36.25" - 920mm |
| HRSC-M-2-DWS | DROP DOWN SIDE WORK SHELF (EXTENDED) | 39" - 991mm | 37" - 940mm | 36.25"- 920mm |
| HRSC-M-2-OS4 | 4 PAN OVERSHELF | 32" - 813mm | 37" - 940mm | 53.75" - 1365mm |
| HRSC-M-2-OS4-DWS | 4 PAN OVERSHELF & SIDE DROP WORK SHELF (EXTENDED) | 39" - 991mm | 37" - 940mm | 53.75" - 1365mm |





