



VACUUM SEALER SU-520GP+

Tabletop model. 20m³/h. 420+420 mm.



FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ Bluetooth connectivity and connection for printer (P models).
- ✓ PLUS welding for retort pouches (+ models).
- ✓ Inert gas flush (G models).
- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

ACCESSORIES

- Bag cutting kits
- Filling plates
- Liquid insert plates
- Vac-norm external vacuum kits
- Vac-norm containers
- Smooth bags for vacuum packing
- Trolley for vacuum packing machines
- Thermal labels for CG2 / RB printer
- RB Desktop printer for SU vacuum packing machines *
- Thermal transfer labels for RB printer



SALES DESCRIPTION

Two sealing bars (420+420 mm.)
20 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Long-shaped chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.



sammic | www.sammic.us
Food Service Equipment Manufacturer

usa@sammic.com phone +1 (224) 307-2232
1225 Hartrey Avenue toll free +1 844 275 3848
60202-1056 Evanston, IL



Project	Date
Item	Qty
Approved	

product sheet
updated 09/23/20



VACUUM SEALER SU-520GP+

Tabletop model. 20m³/h. 420+420 mm.



SPECIFICATIONS

Pump capacity: 700 cf/h
Bar length: 16.5 “
Total loading: 1 Hp
Vacuum pressure (maximum): 2 mbar

Internal dimensions

- ✓ Width: 17 “
- ✓ Depth: 16 “
- ✓ Height: 7.2 “

External dimensions (WxDxH)

- ✓ Width: 24.6 “
- ✓ Depth: 21.1 “
- ✓ Height: 23.4 “ (120V) / 20.1 “ (230V)

Net weight: 180.2 lbs.

Noise level (1m.): 75 dB(A)
Background noise: 32 dB(A)

Crated dimensions

23.8 x 30.6 x 25.6 “
Gross weight: 187.4 lbs.

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - “SENSOR ULTRA” LINE

AVAILABLE MODELS

1140801 Vacuum packing machine SU-520P 120/50-60/1

1140804 Vacuum packing machine SU-520GP 120/50-60/1

1140806 Vacuum packing machine SU-520GP+ 120/60/1

* Ask for special versions availability

 sammic www.sammic.us Food Service Equipment Manufacturer usa@sammic.com phone +1 (224) 307-2232 1225 Hartrey Avenue toll free +1 844 275 3848 60202-1056 Evanston, IL		Project	Date
		Item	Qty
		Approved	

product sheet
updated 09/23/20