

Electronic thermostat with external digital LED display for accurate control and easy reading.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Six adjustable, heavy-duty epoxy-coated wire shelves.

Exterior cabinet contruction consists of full stainless steel front and sides.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Bottom mounted compressor for more efficient operation in coolest area of kitchen.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.

Easy-to-mount plate casters (two lockable) are standard with all units.



CR54SD REACH-IN REFRIGERATOR

Vaulted self-closing doors that remain open at 90 degrees.

Magnetic door gasket is removable and replaceable without tools.

Field reversible, lockable door with foamed-in-place recessed handle.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Unit holds full size sheet pans front to back.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas

Environmentally friendly R290 Hydrocarbon gas.

Tested to NSF Standard 7 requirements for food storage

Standard with full three-year parts and labour warranties and a five-year compressor warranty.

Celco Model	Temperature range	Refrigerant	Number Of Doors	Number Of Shelves	Nema Plug	Dimensions (Inches) ^{WxDxH}
CR54SD	33°F ~ 41°F	R290	2	6	5-15P	53.94 x 31.89 x 82.28
832(108)	53.9(1370) -==	76.8119500		2223(567) 2223(567) 2223(567) 26.2(665) 26.2(146	Intertek

Ceicoinc. FOOD SERVICE EQUIPMENT

In the interest of continuous improvement, specifications are subject to change.

585 Secretariat Court, Mississauga, Ontario, L5S 2A5 phone: 905-364-5200 1-866-77CELCO (23526) fax: 905-364-5205 email: info@celco.ca

www.celco.ca