

CUC48F UNDER-COUNTER FREEZER

Interior cabinet walls are constructed of white epoxy coated steel liner with full hi-level stainless steel coved corner floor.

Exterior cabinet contruction consists of full stainless steel front and sides.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

Two adjustable, heavy-duty epoxy coated wire shelves.

All units come standard with heavyduty worktop surface.

Vaulted self closing door that remains open at 90 degrees.

Solid door construction with foamedin-place recessed handle.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Easy to mount plate casters (two lockable) are standard with all units.

Environmentally friendly R290 Hydrocarbon gas.


Magnetic door gasket is removable and replaceable without tools.


Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Tested to NSF Standard 7 requirements for food storage.

Standard with full three-year parts and labour warranties and a five-year compressor warranty.

Celco Model	Temperature range	Refrigerant	Number Of Doors	Number Of Shelves	Nema Plug	Dimensions (Inches) ^{WxDxH}
CUC48F	-10°F ~ 10°F	R290	2	2	5-15P	48.23 x 29.92 x 35.51





Ceicoinc. Food service equipment

In the interest of continuous improvement, specifications are subject to change.

585 Secretariat Court, Mississauga, Ontario, L5S 2A5 phone: 905-364-5200 1-866-77CELCO (23526) fax: 905-364-5205 email: info@celco.ca

www.celco.ca