MILLENIUM 1375.8MLG/MSG + i

DESIGN

The MILLENIUM range of attractive ergonomically-designed rotisseries, boasts a number of innovative features for increased functionality and are an ideal show-piece used throughout the world in hotels, restaurants and deli stores.

The naked flame from Rotisol's patented burners lick the cast iron hearth creating a spectacular visual, whilst being safe and simple to operate and easy to clean. Spits are driven by individual motors rotating at 2 ½ times per minute allowing meat or poultry to constantly baste itself, sealing in natural juices and cooking to perfection.

FEATURES

- Energy Efficient
- ☐ Independent motors
- 4 tempered glass doors
- ☐ Safety with installed thermocouple
- ☐ Equipped with bottom drip tray with drainage tap
- Powerful halogen lamp.

FINISHES

Standard model in black enamel. A choice of other colours are available. Choses a colour scheme for Millenium.



With chrome or brass trims.





Black and brass finish



ACCESSORIES

A variety of accessories are available for the unit. Video of available accessories and video of vertical spit system.


CUI1375 Anti-cutting prongless spit.		BP1375 Chicken spit.	++++	BRC1375 Basket spit.	
BS1375 Sabre spit for ham / turkey.	+	BRRO1375 Roast-clamp spit.		BA1375 Lamb/suckling- pig spit.	A STATE OF THE STA
BCR1375 Spatchcock chicken spit.		GSV1375 Raised rack for meat storage.		PID1375 Stainless steel tray to unspit.	



MILLENIUM 1375.8MLG/MSG + i

Front view Side view Rotisserie with roof (optional) Rotisserie with roof (optional) and base on casters (optional) and base on casters (optional) (lamps 2x25W) **ROTISSERI**E Illuminated Sign (Optional) Protective Roof (Optional) 90 4 1425 500 GRANDES FLAMMES MILLENIUM securit glass 620 Electrical and Gas Connection, in real 'n Base (Optional) 655 145 1375 195 Short Base (Optional) 1375 605 Custom Base Cabinet (Optional) Φ

Top view Rotisserie with roof (optional) and base on casters (optional)





Stainless steel finish



SPECIFICATIONS

5. 20. 10. 115. 15				
Gas Power	Natural : 123000 BTU/h ; Propane : 112000 BTU/h.			
Gas minimum pressure	Natural : 17,4 mbar. Propane : 27,4 mbar.			
Gas connector	³¾" male			
Electricity	208-230 Volts 1 phase + neutral + earth			
Capacity	40/48 poultries			
Warranty	1 year parts and labor			
Venting	Hood installed conformly with all local codes			
Minimum clearance	21/2" on the right, left and rear side			
Shipping weight	300 kg			

Revised: February 2017

Rotisol S.A.S.

Zone industrielle La Trentaine, Avenue Gustave Eiffel 77507 Chelles cedex - FRANCE

s.bennell@rotisol.com - Tel: +33 1 64 21 80 00

www.rotisol.com

Celco Inc.

www.celco.ca

585 Secretariat Court, Mississauga, Ontario, L5S 2A5 (905) 364-5200 1-866-77CELCO (23526) info@celco.ca