COMMERCIAL

Digital Cabinets Pizza Preparation Table, 1 Door with 6GN 1/3 containers - Stainless **Steel (R290)**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738252 (KCHPT50.6)

1-door pizza preparation table, 50", R290 refrigerant gas, +33/+41°F, stainless steel

Short Form Specification

Item No.

1-door pizza refrigerated preparation table. Exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back and side panels in painted aluminium, interior bottom panel in 304 stainelss steel, worktop in 430 stainless steel.

Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances.

Full-depth cutting board of 79x50x19.5 in.

Digital control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing door with 90-degree stay-open feature.

Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certifications.

3/5 Years warranty.

Main Features


- · External temperature display.
- Removable door gasket for easy cleaning operations.
- · Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Digital Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- Heavy duty Vinyl coated steel shelves.


Construction

- Holds 6 1/3 pans.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Insulated lid maintains food freshness.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

APPROVAL:







EI = Electrical connection
RI = Refrigerant Inlet
RO = Refrigerant Outlet

Electric

Supply voltage:

738252 (KCHPT50.6) 115 V/1 ph/60 Hz **Electrical power, max:** 724.5 kW **Plug type:** NEMA 5-15

Key Information:

Gross capacity: 339.8016 lt Capacity (Cu.Ft.) 9.0

Capacity (Cu.Ft.)
Door hinges:

External dimensions, Width: 47 3/8" (1204 mm)
External dimensions, Depth: 32 1/4" (820 mm)
External dimensions, Height: 41 5/16" (1050 mm)

Number and type of doors: 1 Full

Number and type of grids (included):

1 - 638x634

Type of external material: Stainless Steel
Type of internal material: 304 AISI
Warranty: 3 / 5 years

Refrigeration Data

 ${\bf Compressor\ power:}$

Refrigerant type: R290

Operating temperature min.: 33.01 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost







