Pizza Preparation Table,

COMMERCIAL

Digital Cabinets Pizza Preparation Table, 2 Door with 9GN 1/3 containers - Stainless **Steel (R290)**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



738253 (KCHPT72.9)

2-door pizza preparation table, 72", R290 refrigerant gas, +33/+41°F, stainless steel

Short Form Specification

Item No.

2-door pizza refrigerated preparation table. Exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back and side panels in painted aluminium, interior bottom panel in 304 stainelss steel, worktop in 430 stainless steel.

Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances.

Full-depth cutting board of 79x70.79x19.53 in.

Digital control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing doors with 90-degree stay-open feature. Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.

ETL Safety and Sanitation certifications.

3/5 Years warranty.

Main Features


- · External temperature display.
- · Removable door gasket for easy cleaning operations.
- · Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Electronic Digital Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- · Cabinet and door insulated with high density polyurethane for low environmetal impact.
- Heavy duty Vinyl coated steel shelves.


Construction

- Self-closing door with 90-degree stay-open feature.
- · Heavy duty casters.
- Insulated lid maintains food freshness.
- Holds 9 1/3 pans.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

APPROVAL:







Electrical connection Refrigerant Inlet RI = Refrigerant Outlet RO =

Electric

Supply voltage:

738253 (KCHPT72.9) 115 V/1 ph/60 Hz Electrical power, max: 776.25 kW **NEMA 5-15** Plug type:

Key Information:

Gross capacity: 622.9696 It Capacity (Cu.Ft.) 16.0

Door hinges:

External dimensions, Width: 70 13/16" (1798 mm) External dimensions, Depth: 32 1/4" (820 mm) External dimensions, Height: 41 5/16" (1050 mm)

Number and type of doors: 2 Full

Number and type of grids

(included): 2 - 611x634 Type of external material: Stainless Steel Type of internal material: **304 AISI** Warranty: 3 / 5 years

Refrigeration Data

Compressor power:

R290 Refrigerant type: Operating temperature min.: 33.01 °F Operating temperature max.: 41 °F Condenser type: Fin & tube Defrost type: Auto Defrost







