

How to install your Eazywallz door mural?

Before you begin:

Only apply on a flat, smooth and clean door.

If the door has been freshly painted, please wait at least 1 week for the paint to fully cure. Bubbles can occur if the paint is still outgassing/flashing off.

Installation is recommended no longer than 2 weeks after receipt. No warranty will be valid if installation is past 4 weeks.

What you might need:

A trimming tool (Xacto knife).

A rubber or soft squeegee.

A short ladder or step stool.

A dry cloth.

STEP 1: PREP YOUR DOOR

Clean your door surface. Be sure it is smooth, dry and free of dust and dirt.

Remove the door handle if possible.

STEP 2: GETTING READY

Unpack and spread out the door mural on a large table or clean, hard floor, design face up.

Peel off the liner a few inches only across the top of the door mural. Do not peel off the entire backing at once!

STEP 3: STICK IT!

Stick the top of the panel to the top of the door. Then, using a squeegee or credit card, smooth the top of the mural onto the door. Apply even, firm pressure to ensure complete removal of any bubbles.

Gradually peel the rest of the backing paper off - 6 inches or so at a time - and apply the rest of the door mural.

STEP 4: FINISHING

Bubbling may occur after the door mural as been applied. Simply take a thumbtack or needle and poke the bubbled area a couple of times, then smooth it out with your hands.

Put the handle back on.

