

## Alair® ANSI • CE •

Straight temples // Integrated nosepiece  
// Custom imprinting available

### Lens and Temples | 7 Variations

- S3210S •• Clear
- S3210ST •• Clear **H2X AF**
- S3220S •• Gray
- S3260S •• Infinity Blue
- S3270S • Silver Mirror
- S3275S • Blue Mirror
- S3280S • I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
S3210S	P Z87 + U6	P Z87 +	Weight: 22 gm	Lens: polycarbonate
S3210ST	P Z87 + U6	P Z87 +	PD: 68 mm	Temples: polycarbonate
S3220S	P Z87 + U6 L2.5	P Z87 +	Bridge: 12 mm	Hinge: polycarbonate
S3260S	P Z87 + S	P Z87 +	Lens base: 9.5 curve	Screw: stainless steel
S3270S	P Z87 + S	P Z87 +	Lens size diagonal: 73 mm	Nosepiece: polycarbonate
S3275S	P Z87 + S	P Z87 +	Lens size vertical: 42 mm	
S3280S	P Z87 + U6 L1.7	P Z87 +	Lens thickness: 2.45 mm	

### Lens Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact

### General Specifications

Weight: 22 gm  
PD: 68 mm  
Bridge: 12 mm  
Lens base: 9.5 curve  
Lens size diagonal: 73 mm  
Lens size vertical: 42 mm  
Lens thickness: 2.45 mm  
Overall length (lens - tip): 158 mm  
Overall width (hinge - hinge): 134 mm  
Closest point between temple tips: 84 mm  
Closest point between lens: 8 mm