

Atrex™ ANSI • CSA •



Foam padding // Built-in rubber nosepiece // Co-injected temples

Black Frame | 3 Variations

- SB10810DT ●● Clear AF
- SB10820DT ●● Gray AF
- SB10880DT ●● I/O Mirror AF

Pearl Gray Frame | 1 Variation

- SPG10810DT ●● Clear AF

Translucent Brown Frame | 1 Variation

- STB10815DT ●● Coffee AF

Red Frame | 1 Variation

- SR10870D ●● Silver Mirror

Restraining Strap

108STRAP



SPG108



SR108



STB108



| Part No. | Lens Marking | Temple Marking |
|------------|-----------------|-------------------------|
| SB10810DT | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| SB10820DT | P Z87 + U6 L3 | P Z87 + / P c SEI Z94.3 |
| SB10880DT | P Z87 + U6 L1.7 | P Z87 + / P c SEI Z94.3 |
| SPG10810DT | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| SR10870D | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| STB10815DT | P Z87 + U6 L3 | P Z87 + / P c SEI Z94.3 |

| General Specifications |
|---|
| Weight: 34.22 gm |
| PD: 64 mm |
| Bridge: 16 mm |
| Lens base: 8 curve |
| Lens size diagonal: 63 mm |
| Lens size vertical: 37.5 mm |
| Lens thickness: 2.0 mm |
| Overall length (lens - tip): 166 mm |
| Overall width (screw - screw): 136.3 mm |

| Materials |
|---|
| Lens: polycarbonate |
| Frame: polycarbonate & foam |
| Temples: polycarbonate & thermoplastic elastomers (TPE) |
| Nosepiece: thermoplastic rubbers (TPR) |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light
 L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices